


USB 3.1 Gen 2 (10Gbps) single-bay dock for 2.5"/3.5" SATA SSD/HDD

StarTech ID: SDOCKU313



Unleash the power of USB 3.1 Gen 2 (10 Gbps) with this single-drive docking station. It supports both 2.5" and 3.5" form factors for solid-state and hard drives, with a high drive capacity of 6TB.

Harness the speed of USB 3.1 Gen 2



USB 3.1 Gen 2 gives you greater bandwidth and speed with file transfer rates of up to 10 Gbps – twice the speed of USB 3.0 (USB 3.1 Gen 1) technology. It lets you leverage the high performance of the latest SSDs and hard drives, while alleviating bottlenecks in your data transfers.

Top-loading design for easy drive access

It's never been easier to dock and swap drives from your desktop computer or laptop. Simply insert your drives into the top loading slot, with no tools or trays required. The HDD ejection button allows fast and simple drive removal.



Convenient compatibility

The docking station comes with a USB Type-A to B cable, providing backward compatibility with your existing USB 3.0, 2.0 and 1.x devices. It also supports UASP for enhanced performance.

The SDOCKU313 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Perfect for system builders and IT professionals who need quick access to drives for imaging
- Back up data guickly to an external drive for archiving
- Transfer data from one hard drive to another
- Easily take backup data to an offsite location for safekeeping

Features

- Access data from one 2.5 or 3.5" SATA SDD/HDD over ultra-fast USB 3.1 Gen 2
- Access drives at full speed with support of SATA I, II and III (up to 6 Gbps)
- Top-loading design with built-in ejection button for easy drive access
- UASP support for enhanced performance
- Supports large drive capacity of up to 6TB
- Multi-function LED indicators
- Backward compatible with USB 3.0, 2.0 and 1.x





Technical Specifications

Warranty 2 Years

Bus Type USB 3.1 Gen 2

Chipset ID ASMedia - ASM1351

Compatible Drive Types (Type and Rate) SATA

Drive Installation Removable
Drive Size 2.5in & 3.5in

Fan(s)

Interface USB 3.1 Gen 2

Number of 2.5 inch bays 2 Number of Drives 1

Max Drive Capacity Currently tested with hard drives up to 6TB at 7200 RPM

Maximum Data Transfer Rate 10 Gbps

Type and Rate USB 3.1 Gen 2 - 10 Gbit/s

Type and Rate SATA III (6 Gbps)

UASP Support Yes

Drive Connectors 1 - SATA Data & Power Combo (7+15 pin) Receptacle

Host Connectors 1 - USB 3.1 USB type Micro-B (10 pin; Gen 2; 10 Gbps) Female

Color Black Enclosure Type Plastic

Product Height 2.6 in [65.2 mm]
Product Length 5.7 in [145 mm]
Product Weight 14.1 oz [400 g]
Product Width 3.7 in [93 mm]

LED Indicators 1 - Power & Activity

Center Tip Polarity Positive Input Current 0.8

Input Voltage 110 ~ 240 AC

Output Current 2A
Output Voltage 12 DC
Plug Type M

Power Source AC Adapter Included Humidity 20% ~ 80% RH

Operating Temperature 5°C to 35°C (35°F to 95°F)



Hard-to-find made easy®

Spec Sheet

Storage Temperature

Included in Package

-20°C to 50°C (-4°F to 122°F)

1 - USB 3.1 HDD Dock

1 - USB 3.0 Cable

1 - Universal Power Adapter

4 - Power Adapter Plug (NA/EU/UK/AUS)

1 - Quick Install Guide

Certifications, Reports and Compatibility





