

Cisco Compatible Gigabit RJ45 Copper SFP Transceiver Module - Mini-GBIC

StarTech ID: SFPC1110



The SFPC1110 Cisco Compatible Gigabit RJ45 Copper SFP Transceiver Module (Mini-GBIC) is built to comply with MSA (Multi-Sourcing Agreement) standards to offer a cost-effective way to add, replace or upgrade a copper Ethernet port on your 10/100/1000 Base-T networking equipment.

Featuring 10/100/1000 Mbps Auto-negotiation at distances up to 100m (330 feet), this Ethernet SFP module can be installed into any fiber networking devices with an MSA or Cisco compliant SFP port. Delivering convenience and scalability, this copper transceiver is fully hot-pluggable, allowing you to install the module without interrupting network traffic or requiring a device reboot.

This SFP module is compatible with the Cisco SFP-GE-T transceiver.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications

- Replacing defective or damaged SFPs in MSA compliant or Cisco equipment
- Expand your network to remote segments





Features

- Up to 1.25 Gbps bi-directional communication
- 10/100/1000 Mbps Auto-Negotiation
- Complies with SFP Multi-Source Agreements standards (MSA)
- RJ45 Ethernet connector
- Fully Hot Pluggable
- Auto crossover (MDI / MDI-X) detection
- Compatible with Cisco equipment

Technical Specifications

Warranty 3 Years

Industry Standards IEEE 802.3 10BASE-T

Industry Standards IEEE 802.3ab 1000BASE-T Industry Standards IEEE 802.3u 100BASE-TX

Local Unit Connectors 1 - RJ-45 Female

Maximum Data Transfer Rate 1.25 Gbps

Max Transfer Distance 100 m (328 ft)

DDM No

Compatible Networks 10/100/1000 Mbps

Auto MDIX Yes

Product Length 2.8 in [70 mm]
Product Width 0.5 in [13 mm]
Product Height 0.5 in [13 mm]
Product Weight 0.7 oz [21 g]

Operating Temperature 0°C to 70°C (32°F to 158°F)
Storage Temperature -40°C to 85°C (-40°F to 85°F)

Humidity 30~70% RH Shipping (Package) Weight 0.1 lb [0.1 kg]

Included in Package 1 - 10/100/1000 Mbps RJ45 SFP





Certifications, Reports and Compatibility







