

# 45U SmartRack 4-Post Open Frame Rack, 1000-lb. Capacity - Organize and Secure Network Rack Equipment

MODEL NUMBER: SR4POST



#### **Highlights**

- 45U 4-post open frame rack
- Black steel with square, numbered mounting holes
- Toolless button holes to accept
  PDUs or cable managers

#### Package Includes

- SR4POST
- Installation hardware
- 50x pieces of M6 cage nuts, screws, and washers for equipment mounting
- Cable management hooks
- Owner's manual with warranty information

### **Description**

SmartRack 4-post open frame racks are ideal for cost conscious 19 inch rack mount applications. Multiple units can be bolted together side by side.

#### **Features**

- Supports 1000lbs of rackmount equipment
- Adjustable mounting depth (22 to 39 inches)
- · Textured powder coat finish
- Heavy-duty cold-rolled steel construction
- · Numbered mounting positions
- Bolt down provisions
- · Self squaring design
- Includes mounting hardware of 50 pieces of M6 cage nuts, 50 pieces of M6 screws, and washers
- · Black finish
- Easy assembly

## **Specifications**

OVERVIEW	
Style	4-Post
PHYSICAL	
Installed Whole System Maximum Rack Depth (in.)	39.3





Installed Whole System Maximum Rack Depth (cm)	99.82	
Installed Whole System Minimum Rack Depth (in.)	22.3	
Installed Whole System Minimum Rack Depth (cm)	56.642	
Rack Height (U Spaces)	45	
Shipping Dimensions (hwd / in.)	6 x 4 x 85	
Shipping Dimensions (hwd / cm)	15.24 x 10.16 x 216	
Shipping Weight (lbs.)	55	
Shipping Weight (kg)	24.75	
Unit Dimensions (hwd / in.)	84.3 x 20.2 x 22-39.3	
Unit Weight (lbs.)	54	
Unit Weight (kg)	24.3	
Unit Dimensions (cm)	214.12 x 51.3 x 55.9~99.1 (depth adjustable)	
Color	Black	
Weight Capacity - Stationary (lbs.)	1000	
Weight Capacity - Stationary (kg)	453.6	
Hinged (Swings Away from Wall Bracket)	No	
SPECIAL FEATURES		
Grounding Lug	Includes screws, washers, and bolts to secure user-supplied grounding wire to front or back frames	
CERTIFICATIONS		
NOM (Mexico)	Tested to NOM (Mexico)	
Approvals	EIA-310-D, IEC 60297-3-100, DIN 41494, RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	5-year limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.