

## 2 Port Professional USB KVM Switch Kit with Cables

StarTech ID: SV231USBGB



The SV231SUBGB 2 Port Professional USB KVM Switch Kit with Cables offers simple control of 2 computers from a single monitor/display and USB peripheral set (keyboard, mouse).

The 2 Port KVM includes 2 USB KVM cables, for a complete out-of-the-box solution saving you time and money. An integrated 3 port USB hub allows you to share USB peripherals between computers as though they were connected directly. A compact form factor and rear-port connections minimizes disruption to your workspace.

This OS independent KVM supports resolutions up to 1920x1440, and provides a smooth operating experience in mixed (Windows/Mac/Linux) environments.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

### Användning

- Dual system control for a single workstations increasing user productivity in the office
- Provide centralized control for multiple high-res Digital Signage server control
- Great for manufacturing line computer control, simplifying access to multiple systems
- Perfect for PC test/burn-in computer control saving the desk space required for two monitors, keyboards and mice



### **Funktioner**

- Control 2 computers from one USB keyboard/mouse/monitor
- Share 3 different USB peripherals using the integrated hub
- High 1920x1440 resolution capability
- Front panel push buttons for easy computer selection
- OS independent No software or drivers required
- Supports keyboard and mouse plug and play
- Selectable auto scan time interval
- Supports DDC2B VGA monitors
- Universal Power Adapter with EU and UK prong types included



### Tekniska specifikationer

Daisy-Chain

Warranty 3 Years

No Audio **KVM Ports** 2 **USB** PC Interface PC Video Type VGA Multi-Monitor No Rack-Mountable No Cables Included Yes 1U U Height

Console Interface(s) 1 - VGA (15 pin; High Density D-Sub) Female

Console Interface(s) 3 - USB A (4 pin) Female Host Connectors 2 - USB B (4 pin) Female

No

Host Connectors 2 - VGA (15 pin; High Density D-Sub) Male

DVI Support No IP Control No

Maximum Cable Length 5 m [16.4 ft] Maximum Analog Resolutions 1920x1440

Auto Scan 3, 8, 15 & 30 seconds

Maximum Number of Users 1

Port Selection Support Push Button

OS Compatibility OS independent; No software or drivers required

Color Black Enclosure Type Steel

Product Width 124 mm [4.9 in]
Product Height 40 mm [1.6 in]
Product Depth 70 mm [2.8 in]
Product Weight 420 g [14.8 oz]

Power Source AC Adapter Included

Input Voltage 110 ~ 240 AC

Input Current 0.4A
Output Voltage 5 DC
Output Current 2A
Center Tip Polarity Positive



# Hard-to-find made easy®

**Spec Sheet** 

Included in Package 1 - Universal power adapter (EU/UK)

Included in Package 1 - User Manual

## Certifikat, rapporter och kompatibilitet





