

Spec Sheet

1:2 Standalone USB 2.0 Flash Drive Duplicator and Eraser - Flash Drive Copier

StarTech ID: USBDUP12



The USBDUP12 Standalone Flash Drive Duplicator/Eraser offers a quick and easy solution for cloning a USB flash drive to one or two target USB flash drives or erasing up to two thumb drives simultaneously without having to connect the drives to a computer system.

Featuring high performance duplications at up to 1.5GB per minute, the flash drive copier has a lightweight design and user friendly interface that includes an integrated LCD display. The duplicator can copy the entire source drive volume, or for quicker backups just the data on the drive.

In addition, the target USB ports of the duplicator also support connecting to external USB storage devices. The standalone USB duplicator supports copying/cloning to SD/ SDHC/ Micro SD/ MMC/ Mini SD/ CF media through a USB multimedia card reader (sold separately), and to Hard Drives or Solid State Drives through a Hard Drive docking station or USB enclosure.

The Drive Duplicator also functions as a Flash Drive Eraser capable of erasing up to two USB drives simultaneously with several erase modes available including Quick erase and Full erase, as well as Secure erase, which follows the USA Department of Defense (DoD) secure erase standard, passing over the flash drive 3 times to ensure that the data has been completely wiped.

The USBDUP12 Flash Memory Duplicator is backed by a StarTech.com 2-year warranty and free lifetime technical support.



Applications

- Quick, hassle-free USB Flash Drive backups, data recovery and drive erasing
- Bit-by-bit Flash Drive imaging/cloning to create an exact replica of a source USB drive onto two target USB drives
- Law enforcement and forensic technicians who need one or more exact copies of the original USB Flash Drive for testing or investigation purposes
- Thoroughly erasing data from a flash drive, for added data security and peace of mind

Features

- Standalone duplicator, no computer required
- Supports USB 2.0/ USB 1.1 Flash Drives
- Choose to copy either data only or the full storage capacity of the USB drive
- Supports both Asynchronous and Synchronous copy modes, with 64MB of internal memory
- High performance duplication at up to 1.5GB/minute
- Check Capacity/Quality/Speed of the connected USB Flash Drive(s)
- Department of Defense (DoD) secure erase
- Instant power on/off allows for quick and easy duplications
- Lightweight, user-friendly design
- Integrated LCD display for duplication progress and options menu
- Supports duplicating to HDD/ SSD/ SD/ SDHC/ Micro SD/ MMC/ Mini SD/ CF media types through a USB enclosure, dock, or multimedia card reader (sold separately)

Hard-to-find made easy®

Spec Sheet

Technical Specifications

Bus TypeUSB 2.0Number of Drives3Compatible Drive Types (Type and Rate)USB Flash DriveDrive InstallationRemovableBuffer Size64 MBDrive Connectors3 - USB A (4 pin) FemaleMaximum Data Transfer Rate1.5GB per minuteNoteFor duplication, the destination drive must be of equal or greater capacity than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 rm]Product Height5.1 in [25 rm]Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Green (Activity/Successful Copy)Utype110 ~ 240 ACOutput Voltage5 DCOutput Voltage5 DCOutput Qurrent2Preating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature5°C ~ 45°C (41°F ~ 113°F)	Warranty	2 Years
Number3Compatible Drive Types (Type and Rate)USB Flash Drive and Rate)Drive InstallationRemovableBuffer Size64 MBDrive Connectors3 - USB A (4 pin) FemaleMaximum Data Transfer Rate1.5GB per minuteNoteFor duplication, the destination drive must be of equal or greater capacity than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 mm]Product Width5.1 in [130 mm]Product Wight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Green (Activity/Successful Copy)Utupt Voltage10 ~ 240 ACOutput Voltage5 DCOutput Voltage5 DCOutput Voltage5 °C ~ 45°C (41°F ~ 113°F)Storage Temperature5°C ~ 45°C (41°F ~ 113°F) <td>•</td> <td>USB 2.0</td>	•	USB 2.0
and Rate)RemovableDrive InstallationRemovableBuffer Size64 MBDrive Connectors3 - USB A (4 pin) FemaleMaximum Data Transfer Rate1.5GB per minuteNoteFor duplication, the destination drive must be of equal or greater capacity than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 mm]Product Width5.1 in [130 mm]Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage5 DCOutput Voltage5 DCOutput Voltage5 DCOutput Qurrent2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity19.4 oz [550 g]		3
Buffer Size64 MBDrive Connectors3 - USB A (4 pin) FemaleMaximum Data Transfer Rate1.5GB per minuteNoteFor duplication, the destination drive must be of equal or greater capacity than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 mm]Product Width5.1 in [130 mm]Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Green (Activity/Successful Copy)LED Indicators5 DCOutput Voltage5 DCOutput Voltage5 DCOutput Voltage9 PositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity19.4 oz [550 g]		USB Flash Drive
Drive Connectors3 - USB A (4 pin) FemaleMaximum Data Transfer Rate1.5GB per minuteNoteFor duplication, the destination drive must be of equal or greater capacity than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 mm]Product Height5.1 in [130 mm]Product Width6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage10 ~ 240 ACOutput Voltage5 DCOutput Voltage9 ositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature5°C ~ 45°C (41°F ~ 113°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Drive Installation	Removable
Maximum Data Transfer Rate1.5GB per minuteNote1.5GB per minuteNote1.5GB per minuteNoteFor duplication, the destination drive must be of equal or greater capacity than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 mm]Product Width5.1 in [130 mm]Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage10 ~ 240 ACOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Buffer Size	64 MB
NoteFor duplication, the destination drive must be of equal or greater capacitly than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 mm]Product Width5.1 in [130 mm]Product Height1 in [25 mm]Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Voltage5 DCOutput Qurrent2Plag TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Drive Connectors	3 - USB A (4 pin) Female
than the source drive.ColorBlackEnclosure TypePlasticProduct Length4.7 in [120 mm]Product Width5.1 in [130 mm]Product Height1 in [25 mm]Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Maximum Data Transfer Rate	1.5GB per minute
Enclosure Type Plastic Product Length 4.7 in [120 mm] Product Width 5.1 in [130 mm] Product Height 1 in [25 mm] Product Weight 6.7 oz [190 g] LED Indicators 3 - Green (Activity/Successful Copy) LED Indicators 3 - Red (Error) Power Source AC Adapter Included Input Voltage 10 ~ 240 AC Output Voltage 5 DC Output Current 2 Center Tip Polarity Positive Plug Type H Operating Temperature 5°C ~ 45°C (41°F ~ 113°F) Storage Temperature -20°C ~ 85°C (-4°F ~ 185°F) Humidity 5% ~ 95% RH Package Quantity 1 Shipping (Package) Weight 19.4 oz [550 g]	Note	
Product Length4.7 in [120 mm]Product Width 5.1 in [130 mm]Product Height1 in [25 mm]Product Weight 6.7 oz [190 g]LED Indicators 3 - Green (Activity/Successful Copy)LED Indicators 3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage $110 \sim 240$ ACOutput Voltage 5 DCOutput Current 2 Center Tip PolarityPositivePlug TypeHOperating Temperature $5^{\circ}C \sim 45^{\circ}C (41^{\circ}F \sim 113^{\circ}F)$ Storage Temperature $-20^{\circ}C \sim 85^{\circ}C (-4^{\circ}F \sim 185^{\circ}F)$ Humidity $5\% \sim 95\%$ RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Color	Black
Product Width5.1 in [130 mm]Product Height1 in [25 mm]Product Weight 6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature 5° C ~ 45°C (41°F ~ 113°F)Storage Temperature -20° C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Enclosure Type	Plastic
Product Height1 in [25 mm]Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Product Length	4.7 in [120 mm]
Product Weight6.7 oz [190 g]LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Product Width	5.1 in [130 mm]
LED Indicators3 - Green (Activity/Successful Copy)LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Product Height	1 in [25 mm]
LED Indicators3 - Red (Error)Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Product Weight	6.7 oz [190 g]
Power SourceAC Adapter IncludedInput Voltage110 ~ 240 ACOutput Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	LED Indicators	3 - Green (Activity/Successful Copy)
Input Voltage 110 ~ 240 AC Output Voltage 5 DC Output Current 2 Center Tip Polarity Positive Plug Type H Operating Temperature 5°C ~ 45°C (41°F ~ 113°F) Storage Temperature 5°C ~ 85°C (-4°F ~ 185°F) Humidity 5% ~ 95% RH Package Quantity 1 Shipping (Package) Weight 19.4 oz [550 g]	LED Indicators	3 - Red (Error)
Output Voltage5 DCOutput Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Power Source	AC Adapter Included
Output Current2Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Input Voltage	110 ~ 240 AC
Center Tip PolarityPositivePlug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Output Voltage	5 DC
Plug TypeHOperating Temperature5°C ~ 45°C (41°F ~ 113°F)Storage Temperature-20°C ~ 85°C (-4°F ~ 185°F)Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Output Current	2
Operating Temperature $5^{\circ}C \sim 45^{\circ}C (41^{\circ}F \sim 113^{\circ}F)$ Storage Temperature $-20^{\circ}C \sim 85^{\circ}C (-4^{\circ}F \sim 185^{\circ}F)$ Humidity $5\% \sim 95\%$ RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Center Tip Polarity	Positive
Storage Temperature $-20^{\circ}C \sim 85^{\circ}C (-4^{\circ}F \sim 185^{\circ}F)$ Humidity $5\% \sim 95\%$ RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Plug Type	Н
Humidity5% ~ 95% RHPackage Quantity1Shipping (Package) Weight19.4 oz [550 g]	Operating Temperature	5°C ~ 45°C (41°F ~ 113°F)
Package Quantity1Shipping (Package) Weight19.4 oz [550 g]	Storage Temperature	-20°C ~ 85°C (-4°F ~ 185°F)
Shipping (Package) Weight 19.4 oz [550 g]	Humidity	5% ~ 95% RH
	Package Quantity	1
Included in Deckerson d. Durliceter	Shipping (Package) Weight	19.4 oz [550 g]
included in Package 1 - Duplicator	Included in Package	1 - Duplicator
Included in Package 1 - Universal Power Adapter	Included in Package	1 - Universal Power Adapter
Included in Package 3 - Power Adapter Plug (NA/ UK/ EU)	Included in Package	3 - Power Adapter Plug (NA/ UK/ EU)
Included in Package 1 - Instruction Manual	Included in Package	1 - Instruction Manual



Spec Sheet

Certifications, Reports and Compatibility





www.startech.com 1 800 265 1844