

www.tripplite.com



USB-C to HDMI Adapter with USB-A Hub, Gigabit Ethernet, Thunderbolt 3, 1080p - PD Charging, Black

MODEL NUMBER: U444-06N-HGUB-C











Features

Mini Docking Station Turns Your Device's USB-C or Thunderbolt 3 Port into a Multiport Workstation This USB-C to HDMI cable expands the potential of your tablet, laptop, Chromebook, MacBook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for transmitting digital audio and 1080p video to a large display, adding a thumb drive or other USB peripheral, powering and charging a PD Charging-compliant mobile device, and connecting to a Gigabit Ethernet network—all at the same time.

Supports USB DisplayPort Alternate Mode for Transmitting Audio/Video DisplayPort and USB Signals With a source device that also supports USB DisplayPort Alt Mode, you can extend video from your primary display to another, duplicate the same video on both displays, or change the second display to your primary.

Transmits Crystal-Clear 1080p Video and Digital Audio to an HDMI Display

To send digital audio and HD video to an HDMI television, projector or monitor, connect the HDMI port to the display using an HDMI cable (sold separately). The HDMI port supports HD video resolutions up to $1920 \times 1080 (1080p)$ at 60 Hz.

Connects a USB Peripheral

The USB-A port accepts USB peripherals, such as a flash drive, mouse, keyboard or printer. It supports fast USB 3.1 Gen 1 data transfer rates up to 5 Gbps and is backward compatible with USB 2.0 and USB 1.1 devices.

Charges a Connected Device

The USB-C Power Delivery (PD) port provides power and charging to the PD Charging-compliant device (such as a MacBook, Chromebook or Android smartphone) the U444-06N-HGUB-C is connected to.

Highlights

- Transmits DisplayPort signals from sources supporting USB DisplayPort Alt Mode
- Delivers HD picture quality at resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Connects you to a wired
 Ethernet network when no Wi-Fi is available
- Powers and charges PD
 Charging-compliant devices,
 such as MacBooks and
 Chromebooks
- Easy installation with plug-andplay operation—no software required

Applications

- Play video from your laptop or PC on an HDMI display, such as an HDTV or projector
- Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Transfer data from a USB flash drive or connect your computer to a USB printer or other USB device
- Charge your connected notebook or laptop by connecting its wall charger to the USB-C PD Charging port

System Requirements

 Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 3A (60W).

Accesses a Wired Gigabit Ethernet Network

The RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Built-In USB-C Cable Connects in Either Direction

Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Ready to Use Right Out of the Package

The plug-and-play USB 3.1 to HDMI adapter requires no software, drivers or external power. The compact unit fits easily into a pocket, briefcase or laptop bag for connecting on the go.

3-Year Warranty and Environmentally Responsible Design

The U444-06N-HGUB-C comes with a 3-year warranty. It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

 Display device with HDMI input (HDMI port)

Package Includes

- U444-06N-HGUB-C USB-C to HDMI Adapter with USB-A Hub, Gigabit Ethernet, Thunderbolt 3, 1080p—PD Charging, Black
- Owner's manual

Specifications

MODEL TEXT		
What Does This Product Do?	Adds HDMI, USB-A, USB-C PD charging and Gigabit Ethernet ports to your tablet, laptop, notebook, smartphone or PC.	
OVERVIEW		
Over Current Protection		
INPUT		
Cable Length (ft.)		
Cable Length (m)		
Cable Length (in.)		
Built-In Cable Length (ft.)		
Built-In Cable Length (m)		
Built-In Cable Length (in.)		
Built-In Cable Length (cm)		
External Power Supply Input Specs (V / Hz / A)		
External Power Supply Output Specs (V / A)		





External Power Supply Cord Length (ft.)		
External Power Supply Cord Length (m.)		
Bus Powered	Yes	
Cable Length (cm)		
Product Length (in.)	6.00	
Product Length (cm.)		
Product Length (ft.)		
Product Length (m.)		
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators		
PHYSICAL		
Shipping Dimensions (hwd / in.)	5.5 x 3.9 x 0.91	
Shipping Weight (lbs.)	0.10	
Unit Packaging Type	Box	
Unit Dimensions (hwd / in.)	0.57 x 1.57 x 3.15	
Unit Weight (lbs.)	0.09	
Unit Weight (kg)	0.04	
Material of Construction	PVC and ABS	
Color	Black	
Transmitter Unit Dimensions (hwd / in.)		
Transmitter Unit Dimensions (hwd / cm.)		
Receiver Unit Dimensions (hwd / in.)		
Receiver Unit Dimensions (hwd / cm.)		
Transmitter Unit Weight (lbs.)		
Transmitter Unit Weight (kg)		
Receiver Unit Weight (lbs.)		
Receiver Unit Weight (kg)		
Cable Jacket Rating	VW-1	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 F (0 to 45 C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	





Relative Humidity		
Operating Elevation (ft.)		
Storage Elevation (ft.)		
BTUs	9 BTU/Hr	
Power Consumption (Watts)	2.6	
Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 90% RH, Non-Condensing	
Power Provided to Connected Device(s)		
COMMUNICATIONS		
Signal Range (ft.)		
Network Speed	1Gbps	
IEEE Standards Supported	802.3; 802.3u; 802.3az; 802.3x	
CONNECTIONS		
Ports	4	
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	HDMI (FEMALE)	
Side B - Connector 2	USB 3.0 A (FEMALE)	
Side B - Connector 3	USB C (FEMALE)	
Side B - Connector 4	RJ45 (FEMALE)	
Connector Plating	Nickel	
PORT EXPANSION		
Max Distance (Between any 2 Units)		
FEATURES & SPECIFICATIONS		
Max Supported Video Resolution	1080p (1920 x 1080) @60Hz	
HDMI Specification	1.3	
HDCP Specification	1.3	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Audio Specification		
Driver Required	No	
Recommended Category Cable	Cat5/Cat5e/Cat6 Cables	
USB Power Delivery (PD) Charging Support	Yes	
Auto MDIX Support	Yes	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Full Duplex Support	Yes	
Suspend Mode Support	Yes	
Remote Wakeup Support	Yes	
CERTIFICATIONS		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies