

USB 3.0 to HDMI External Video Card Multi Monitor Adapter with 1-Port USB Hub – 1920x1200 / 1080p

StarTech ID: USB32HDEH



The USB32HDEH USB 3.0 to HDMI® Adapter turns a USB 3.0 port into an HDMI output port with 1920x1200/1080p video support. The adapter features built-in USB 3.0 pass-through, which offers a connection port in place of the USB port used for connecting the HDMI adapter – an ideal workaround for Ultrabook™ or laptop users, where only a limited number of USB ports are available.

Functioning as an external graphics card, this USB to HDMI adapter provides a convenient way to add multimonitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your HDMI display / projector. The adapter can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity. The included HDMI to DVI adapter also allows you to use this device with a DVI display.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher



Applications

- Add a secondary HDMI display with full HD capability
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations
- View large or multiple spreadsheets across several displays
- Use the adapter to connect your PC to your HDMI-equipped projector or display for viewing family pictures and movies
- Great for researchers and writers offering the ability to have reference material on one display and a working document copy on the other
- Run multiple applications on different screens check your email on one display and search the web on the other

Features

- High-Definition resolution support (up to 1920x1200/1080p)
- Built in 1-Port USB 3.0 Hub
- SuperSpeed USB 3.0 (5 Gbps) Interface, backward compatible with USB 2.0
- Quick, easy installation
- USB-powered No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the use of multiple USB32HDEH adapters on a single system (up to 5)





Technical Specifications

Warranty 2 Years
Audio Yes
USB Pass-Through Yes

Memory 16MB DDR II

Industry Standards SuperSpeed USB 3.0, USB 2.0

Chipset ID MCT Trigger 5 T5-302

Output Signal HDMI

Connector A 1 - USB 3.0 A (9 pin; SuperSpeed) Male

Connector B 1 - HDMI (19 pin) Female

Connector B 1 - USB 3.0 A (9 pin; SuperSpeed) Female

Maximum Digital 1920x1200

Resolutions

Supported Resolutions Widescreen(16/32 bit):

1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800,

1280x768, 1280x720

Standard(16/32 bit):

1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600

Wide Screen Supported Yes

Audio Specifications 2-Channel Stereo (48Khz)
OS Compatibility Windows 8/8.1 (32/64)
Windows 7(32/64)

Windows 7(32/64)
Windows Vista (32/64)
Windows XP (32/64)
Drivers are WHQL certified

Microsoft WHQL Certified Yes

System and Cable CPU: i3 Dual core 2.8GHz Requirements RAM: 2GB or higher

Full HD Video:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

NoteConnect a maximum of five USB32HDEH adapters on a single PC - See manual for

system requirements

Color Black Enclosure Type Plastic





Hard-to-find made easy®

Cable Length	6.3 in [160 mm]
Product Length	3.3 in [85 mm]
Product Width	1.9 in [49 mm]
Product Height	0.7 in [17 mm]
Product Weight	2.6 oz [75 g]
Power Source	USB-Powered

Operating Temperature 0°C to 50°C (32°F to 122°F)
Storage Temperature -10°C to 75°C (14°F to 167°F)

Humidity < 85% non-condensing

Shipping (Package) 0.5 lb [0.2 kg] Weight

Included in Package 1 - USB 3.0 to HDMI Adapter Included in Package 1 - HDMI to DVI adapter

Included in Package 1 - Software CD

Included in Package 1 - Manual

Certifications, Reports and Compatibility











