



HP 8200 zl Switch Series



Key features

- Core, distribution, mission-critical access layer
- Advanced high-availability AllianceONE integrated
- Layer 2 to 4 and intelligent edge feature set
- Enterprise-class performance and security
- Scalable 10/100/1000 and 10 GbE connectivity

Product overview

The HP 8200 zl Switch Series offers high performance, scalability, and a wide range of features in a high-availability platform that dramatically reduces complexity and provides reduced cost of ownership. As part of a unified wired and wireless network infrastructure solution, the 8200 zl switch series provides platform technology, system software, system management, application integration, wired and wireless integration, network security, and support that are common across HP modular and fixed-port switches. Together, they deliver an agile, cost-effective, high-availability network solution. With key technologies to provide solution longevity, the 8200 zl switch series is built to deliver long-term investment protection without added complexity for network core, aggregation, and high-availability access layer deployments. It provides these capabilities while bringing to market the industry's first highly available switch with a lifetime warranty.

Features and benefits

Software-defined networking

- **NEW OpenFlow**
is a key technology enabling software-defined networking by allowing the separation of data (packet forwarding) and control (routing decision) paths

Quality of Service (QoS)

- **Advanced classifier-based QoS**
classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information; applies QoS policies such as setting priority level and rate limit to selected traffic on a per-port or per-VLAN basis
- **Layer 4 prioritization**
enables prioritization based on TCP/UDP port numbers
- **Traffic prioritization**
allows real-time traffic classification into eight priority levels mapped to eight queues
- **Bandwidth shaping**
 - **Port-based rate limiting**
provides per-port ingress-/egress-enforced maximum bandwidth
 - **Classifier-based rate limiting**
uses an access control list (ACL) to enforce maximum bandwidth for ingress traffic on each port
 - **Guaranteed minimum**
provides per-port, per-queue egress-based guaranteed minimum bandwidth
- **Class of Service (CoS)**
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ

HP AllianceONE integration

- **HP AllianceONE Services zl Module**
allows you to embed applications directly into the network, either distributed throughout the network at the network edge or centralized in the core or distribution layer; for more information about the HP AllianceONE solution, visit the HP website

Management

- **Remote intelligent mirroring**
mirrors selected ingress/egress traffic based on ACL, port, MAC address, or VLAN to a local or remote HP 8200 zl, 6600, 6200 yl, 5400 zl, or 3500 Switch anywhere on the network
- **RMON, XRMON, and sFlow v5**
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
automated device discovery protocol provides easy mapping of network management applications

- **Uni-Directional Link Detection (UDLD)**
monitors a cable between two switches and shuts down the ports on both ends if the cable is broken, turning the bidirectional link into a unidirectional one; this prevents network problems such as loops
- **HP unified core-to-edge device/network management tools**
provide HP networking portfolio-common device-level tools (CLI, Web GUI, and Menu) plus seamless integration into HP PCM+/Identity Driven Manager (IDM) network management deployments
- **Command authorization**
leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; an audit trail documents activity
- **Friendly port names**
allow assignment of descriptive names to ports
- **Dual flash images**
provides independent primary and secondary operating system files for backup while upgrading or fine-tuning the switch configuration
- **Multiple configuration files**
can be stored to the flash image
- **HP unified core-to-edge features**
HP ProVision portfolio-common feature implementation allows faster solution deployment
- **NEW Comware CLI**
 - **Comware-compatible CLI**
bridges the experience of HP Comware CLI users who are using the HP ProVision software CLI
 - **Display and fundamental Comware CLI commands**
are embedded in the switch CLI as native commands; display output is formatted as on Comware-based switches, and fundamental commands provide a Comware-familiar initial switch setup
 - **Configuration Comware CLI commands**
when Comware commands are entered, CLI help is elicited to formulate the correct ProVision software CLI command

Connectivity

- **High-density port connectivity**
provides 12 interface module slots, up to 288 wire-speed 10/100/1000 PoE-enabled ports, or 96 10-GbE ports per system
- **IEEE 802.3az Energy Efficient Ethernet**
lowers power consumption in periods of low-link usage (supported on v2 zl 10/100/1000 and 10/100 modules)
- **IEEE 802.3af Power over Ethernet (PoE)**
provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras
- **IEEE 802.3at Power Over Ethernet Plus**
provides up to 30 W per port to IEEE 802.3 for PoE-/PoE+-powered devices such as video IP phones, IEEE 802.11n wireless access points, and advanced pan/zoom/tilt security cameras

- **Jumbo frames**
on Gigabit Ethernet and 10-Gigabit ports, jumbo frames allow high-performance remote backup and disaster-recovery services
- **HP unified core-to-edge hardware**
HP ProVision family-common interface and service modules, Gigabit optics/10 GbE transceivers, and power supplies enable sparing simplicity
- **Prestandard PoE support**
detects and provides power to prestandard PoE devices; see the list of supported devices in the product FAQs at www.hp.com/networking
- **Auto-MDIX**
automatically adjusts for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- **IPv6**
 - **IPv6 host**
enables switches to be managed in an IPv6 network
 - **Dual stack (IPv4 and IPv6)**
transitions from IPv4 to IPv6, supporting connectivity for both protocols
 - **MLD snooping**
forwards IPv6 multicast traffic to the appropriate interface
 - **IPv6 ACL/QoS**
supports ACL and QoS for IPv6 network traffic
 - **IPv6 routing**
supports static and OSPFv3 routing protocols
 - **6in4 tunneling**
supports encapsulation of IPv6 traffic in IPv4 packets

Performance

- **High-speed, high-capacity architecture**
1.12 Tbps crossbar switching fabric provides intra-module and inter-module switching with 739.2 million pps throughput on the purpose-built HP ProVision ASICs
- **Selectable queue configurations**
allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- **Scalable system design**
chassis architecture/backplane provides built-in performance capacity/headroom to support next-generation high-density/high-speed connectivity

Resiliency and high availability

- **Nonstop switching**
improves network availability to better support critical applications such as unified communication and mobility; interface and fabric modules continue switching traffic during failover from active to standby management module

- **Nonstop routing**
enhances Layer 3 high availability; OSPFv2/v3 and VRRP will continue to operate and route network traffic during failover from an active to a standby management module
- **Redundant management, fabric, and power**
provide enhanced system availability and continuity of operations
- **Distributed trunking**
enables loop-free and redundant network topology without using Spanning Tree Protocol; allows a server or switch to connect to two switches using one logical trunk for redundancy and load sharing
- **IEEE 802.1s Multiple Spanning Tree Protocol**
provides high link availability in multiple VLAN environments by allowing multiple spanning trees; encompasses IEEE 802.1D Spanning Tree Protocol and IEEE 802.1w Rapid Spanning Tree Protocol
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP) and HP port trunking**
support up to 144 trunks, each with up to eight links (ports) per trunk
- **Proven ASIC and system architecture**
the HP ProVision ASIC and platform architecture, leveraged from HP's successful 5400 zl, 3500, 6600, and 6200 yl switch series, reduces technology risk and provides reliable support and flexibility
- **HP zl family components**
employ market-proven intelligent edge switch interface modules, optics, and power supplies to reduce technology risk and enhance system reliability
- **Hot-swappable modules**
interface, management, and fabric modules as well as mini-GBIC optics and power supplies can be removed, swapped, or added to the system without interrupting ongoing switch operations
- **Redundant, hot-swappable cooling**
redundant fan design and hot-swappable fan tray provide continuity of operation in case of a single fan failure
- **Passive system design**
passive chassis backplane (no traffic-forwarding active componentry) provides system reliability and reduces the impact of a component failure
- **Virtual Route Redundancy Protocol**
allows groups of two routers to dynamically back each other up to create highly available routed environments

Layer 2 switching

- **VLAN support and tagging**
supports the IEEE 802.1Q standard and 2,048 VLANs simultaneously
- **IEEE 802.1v protocol VLANs**
isolate select non-IPv4 protocols automatically into their own VLANs
- **GARP VLAN Registration Protocol**
allows automatic learning and dynamic assignment of VLANs

- **IEEE 802.1ad Q-in-Q**
increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network
- **MAC-based VLAN**
provides granular control and security; uses RADIUS to map a MAC address/user to specific VLANs (requires v2 modules)
- **Rapid Per-VLAN Spanning Tree (RPVST+)**
allows each VLAN to build a separate spanning tree to improve link bandwidth usage; is compatible with PVST+
- **HP switch meshing**
dynamically load balances across multiple active redundant links to increase available aggregate bandwidth; allows concurrent Layer 3 routing with v2 modules

Layer 3 services

- **User Datagram Protocol (UDP) helper function**
allows UDP broadcasts to be directed across router interfaces to specific IP unicast or subnet broadcast addresses and prevents server spoofing for UDP services such as DHCP
- **Loopback interface address**
defines an address in Routing Information Protocol (RIP) and OSPF, improving diagnostic capability
- **Route maps**
provide more control during route redistribution; allow filtering and altering of route metrics

Layer 3 routing

- **Static IP routing**
provides manually configured routing for both IPv4 and IPv6 networks
- **Routing Information Protocol (RIP)**
provides RIPv1 and RIPv2 routing
- **OSPF**
provides OSPFv2 for IPv4 routing and OSPFv3 for IPv6 routing
- **Policy-based routing**
uses a classifier to select traffic that can be forwarded based on policy set by the network administrator (requires v2 modules)
- **Border Gateway Protocol (BGP)**
provides IPv4 Border Gateway Protocol routing, which is scalable, robust, and flexible

Security

- **Access control lists (ACLs)**
provide filtering based on the IP field, source/destination IP address/subnet, and source/destination TCP/UDP port number on a per-VLAN or per-port basis

- **Multiple user authentication methods**
 - **IEEE 802.1X users per port**
provides authentication of multiple IEEE 802.1X users per port
 - **Web-based authentication**
authenticates from a Web browser for clients that do not support IEEE 802.1X supplicant
 - **MAC-based authentication**
authenticates client with the RADIUS server based on a client's MAC address
 - **Concurrent IEEE 802.1X, Web, and MAC authentication schemes per port**
accepts up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- **Virus throttling**
detects traffic patterns typical of worm-type viruses and either throttles or entirely prevents the virus from spreading across the routed VLANs or bridged interfaces without requiring external appliances
- **DHCP protection**
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Secure management access**
securely encrypts all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- **Management Interface Wizard**
helps secure management interfaces such as SNMP, telnet, SSH, SSL, Web, and USB at the desired level
- **Switch CPU protection**
provides automatic protection against malicious network traffic trying to shut down the switch
- **ICMP throttling**
defeats ICMP denial-of-service attacks by enabling any switch port to automatically throttle ICMP traffic
- **Identity-driven ACL**
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **STP BPDU port protection**
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **Dynamic IP lockdown**
works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- **Dynamic ARP protection**
blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **Detection of malicious attacks**
monitors 10 types of network traffic and sends a warning when an anomaly that potentially can be caused by malicious attacks is detected

- **Port security**
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout**
prevents particular configured MAC addresses from connecting to the network
- **Source-port filtering**
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**
eases switch management security administration by using a password authentication server
- **Secure Shell**
encrypts all transmitted data for secure remote CLI access over IP networks
- **Secure Sockets Layer (SSL)**
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Secure FTP**
allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Switch management logon security**
can require either RADIUS or TACACS+ authentication for secure switch CLI logon
- **Security banner**
displays a customized security policy when users log in to the switch
- **USB Secure Autorun (requires HP PCM+)**
deploys, diagnoses, and updates a switch using a USB flash drive; works with a secure credential to prevent tampering
- **STP Root Guard**
protects the root bridge from malicious attacks or configuration mistakes
- **Integrated Threat Management applications**
includes advanced, scalable, switch-integrated security tools such as stateful firewall, intrusion detection/prevention system (IDS/IPS), and VPN concentrator via the HP Threat Management Services zl Module

Convergence

- **IP multicast routing**
includes PIM Sparse and Dense modes to route IP multicast traffic
- **IP multicast snooping (data-driven IGMP)**
automatically prevents flooding of IP multicast traffic
- **LLDP-MED (Media Endpoint Discovery)**
is a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones

- **PoE allocations**
support multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user specified) to allocate PoE power for more efficient energy savings
- **Auto VLAN configuration for voice**
 - **RADIUS VLAN**
uses a standard RADIUS attribute and LLDP-MED to automatically configure a VLAN for IP phones
 - **CDPv2**
uses CDPv2 to configure legacy IP phones

Flexibility

- **Unified wired and wireless deployment and management**
employs the MSM765zl mobility controller and offers secure, advanced wireless services with simplified management and unified wired and wireless operation across the network
- **Complete feature set**
provides Gigabit PoE for edge VoIP solutions, scalable 10 GbE for enterprise-class distribution-layer implementations, advanced wireless management for comprehensive mobility solutions, and critical high-availability features for midmarket core network deployments
- **Programmable ASIC design**
allows the seamless addition of new QoS and security features over time without costly hardware upgrades

Warranty and support

- **Lifetime warranty**
for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)†
- **Electronic and telephone support**
limited electronic and telephone support is available from HP; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**
to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zl Modules, HP Threat Management Services zl Module, HP AllianceOne Extended zl Module with Riverbed Steelhead, HP MSM765zl Mobility Controller and HP Survivable Branch Communication zl Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at www.hp.com/networking/warranty.

HP 8200 zL Switch Series

Specifications



HP 8206 zL Switch with Premium Software (J9640A)

HP 8212 zL Switch with Premium Software (J9641A)

Included accessories	1 HP 8200 zL Management Module (J9092A) 2 HP 8200 zL Fabric Module (J9093A) 1 HP 8200 zL System Support Module (J9095A) 1 HP 8200 zL Switch Premium License (J9474A)	1 HP 8200 zL Management Module (J9092A) 2 HP 8200 zL Fabric Module (J9093A) 1 HP 8200 zL System Support Module (J9095A) 1 HP 8200 zL Switch Premium License (J9474A)
Ports	6 open module slots Supports a maximum of 144 autosensing 10/100/1000 ports or 48 10-GbE ports or 144 mini-GBICs, or a combination	12 open module slots Supports a maximum of 288 autosensing 10/100/1000 ports or 96 10-GbE ports or 288 mini-GBICs, or a combination
Power supplies	2 power supply slots 1 minimum power supply required (ordered separately)	4 power supply slots 2 minimum power supplies required (ordered separately)
Physical characteristics	17.42(w) x 17.49(d) x 10.35(h) in (44.25 x 44.42 x 26.29 cm) (6U height) Weight 48.1 lb (21.82 kg)	17.5(w) x 18.7(d) x 15.6(h) in (44.45 x 47.5 x 39.62 cm) (9U height) 50.44 lb (22.88 kg)
Memory and processor	Gigabit module ARM9 @ 200 MHz; packet buffer size: 144 Mb QDR SDRAM 10G module ARM9 @ 200 MHz; packet buffer size: 36 Mb QDR SDRAM Management module Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 128 MB compact flash, 256 MB DDR SDRAM	Gigabit module ARM9 @ 200 MHz; packet buffer size: 144 Mb QDR SDRAM 10G module ARM9 @ 200 MHz; packet buffer size: 36 Mb QDR SDRAM Management module Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 128 MB compact flash, 256 MB DDR SDRAM
Mounting	Mounts in an EIA-standard 19 in telco rack/equipment cabinet (hardware included); horizontal surface mounting only. An optional 4-post cabinet rail is available (see ordering guide).	Mounts in an EIA-standard 19 in telco rack or equipment cabinet (hardware included); horizontal surface mounting only. An optional 4-post cabinet rail is available (see ordering guide).
Performance	1000 Mb Latency < 3.7 μ s (FIFO 64-byte packets) 10 Gbps Latency < 2.1 μ s (FIFO 64-byte packets) Throughput up to 369.6 million pps Routing/Switching capacity 496.8 Gbps Switch fabric speed 561.6 Gbps Routing table size 10000 entries MAC address table size 64000 entries	1000 Mb Latency < 3.7 μ s (FIFO 64-byte packets) 10 Gbps Latency < 2.1 μ s (FIFO 64-byte packets) Throughput up to 739 million pps Routing/Switching capacity 993.6 Gbps Switch fabric speed 1.1 Tbps Routing table size 10000 entries MAC address table size 64000 entries
Environment	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 15% to 95% @ 131°F (55°C), noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 15% to 95% @ 149°F (65°C), noncondensing Altitude up to 10,000 ft (3 km) Acoustic Power: 60.0 dB, Pressure: 41.3 dB; ISO 7779, ISO 9296	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 15% to 95% @ 131°F (55°C), noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 15% to 95% @ 149°F (65°C), noncondensing Altitude up to 10,000 ft (3 km) Acoustic Power: 63.0 dB, Pressure: 47.8 dB; ISO 7779, ISO 9296
Electrical characteristics	Achieved Miercom Certified Green Award	Achieved Miercom Certified Green Award
Description	Chassis ships without power supplies. Two power supply slots are available; three different power supplies are available. See power supply products for additional specifications.	Chassis ships without power supplies. Four power supply slots are available; three different power supplies are available. See power supply products for additional specifications.
Maximum heat dissipation	2450 BTU/hr (2584.75 kJ/hr), (max. non-PoE); 3700 BTU/hr (3903 kJ/hr) (max. PoE)	4900 BTU/hr (5170 kJ/hr), (max. non-PoE); 7400 BTU/hr (7807 kJ/hr) (max. PoE)
Voltage	100-127/200-240 VAC	100-127/200-240 VAC
Frequency	50/60 Hz	50/60 Hz
Notes	Power supplies must be ordered separately. A minimum of one J8712A, J8713A, or J9306A supply is required to power the system.	Power supplies must be ordered separately. A minimum of two J8712A, J8713A, or J9306A supplies are required to power the system.
Safety	CSA 22.2 No. 60950; UL 60950; IEC 60950; EN 60950; IEC 60825	CSA 22.2 No. 60950; UL 60950; IEC 60950; EN 60950; IEC 60825
Emissions	FCC Class A; FCC part 15 Class A; ICE-003, Canadian Radio Interface Regulation; VCCI Class A; EN 55022/CISPR 22 Class A	FCC Class A; FCC part 15 Class A; ICE-003, Canadian Radio Interface Regulation; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity	EN 55024, CISPR 24 EN 61000-4-2; 4 kV CD, 8 kV AD IEC 61000-4-3; 3 V/m IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line) IEC 61000-4-5; 1 kV/2 kV AC IEC 61000-4-6; 3 V	EN 55024, CISPR 24 EN 61000-4-2; 4 kV CD, 8 kV AD IEC 61000-4-3; 3 V/m IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line) IEC 61000-4-5; 1 kV/2 kV AC IEC 61000-4-6; 3 V

HP 8200 zl Switch Series

Specifications (continued)

	HP 8206 zl Switch with Premium Software (J9640A)	HP 8212 zl Switch with Premium Software (J9641A)
Power frequency magnetic field	IEC 61000-4-8; 1 A/m, 50 or 60 Hz	IEC 61000-4-8; 1 A/m, 50 or 60 Hz
Voltage dips and interruptions	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods
Harmonics	EN 61000-3-2, IEC 61000-3-2	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3	EN 61000-3-3, IEC 61000-3-3
Management	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)
Notes	Interface/Service modules, power supplies, and redundant management module must be ordered separately. RS-232C console port via an RJ-45 connector. Supported 1G SFP transceivers are revision "B" or later (product number ends with the letter "B" or later; for example, J9142B, J8177C).	Interface/Service modules, power supplies, and redundant management module must be ordered separately. RS-232C console port via an RJ-45 connector. Supported 1G SFP transceivers are revision "B" or later (product number ends with the letter "B" or later; for example, J9142B, J8177C).
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW442E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW443E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW444E)</p> <p>3-year, 24x7 SW phone support, software updates (UW445E)</p> <p>Installation with minimum configuration, system-based pricing (U4828E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4832E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW462E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW463E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW464E)</p> <p>4-year, 24x7 SW phone support, software updates (UW465E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UY921E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UY922E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY923E)</p> <p>5-year, 24x7 SW phone support, software updates (UY924E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW446E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW466E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UY925E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR609E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR610E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR613E)</p> <p>1-year, 24x7 software phone support, software updates (HR612E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR611E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS762E)</p> <p>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS763E)</p> <p>3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS764E)</p> <p>3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS765E)</p> <p>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS766E)</p> <p>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS767E)</p> <p>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS768E)</p> <p>5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS769E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW447E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW448E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW449E)</p> <p>3-year, 24x7 SW phone support, software updates (UW450E)</p> <p>Installation with minimum configuration, system-based pricing (U4828E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4832E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW467E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW468E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW469E)</p> <p>4-year, 24x7 SW phone support, software updates (UW471E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UY926E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UY927E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY928E)</p> <p>5-year, 24x7 SW phone support, software updates (UY929E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UY937E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW472E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UY930E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR614E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR615E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR618E)</p> <p>1-year, 24x7 software phone support, software updates (HR617E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR616E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS754E)</p> <p>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS755E)</p> <p>3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS756E)</p> <p>3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS757E)</p> <p>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS758E)</p> <p>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS759E)</p> <p>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS760E)</p> <p>5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS761E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

HP 8200 zL Switch Series

Specifications (continued)

	HP 8206 zL Switch with Premium Software (J9640A)	HP 8212 zL Switch with Premium Software (J9641A)	
Standards and protocols (applies to all products in series)	<p>BGP</p> <ul style="list-style-type: none"> RFC 1997 BGP Communities Attribute RFC 2918 Route Refresh Capability RFC 4271 A Border Gateway Protocol 4 (BGP-4) RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP) RFC 4724 Graceful Restart Mechanism for BGP RFC 5492 Capabilities Advertisement with BGP-4 <p>Denial of service protection</p> <ul style="list-style-type: none"> CPU DoS Protection <p>Device management</p> <ul style="list-style-type: none"> RFC 1591 DNS (client) HTML and telnet management <p>General protocols</p> <ul style="list-style-type: none"> IEEE 802.1ad Q-in-Q IEEE 802.1AX-2008 Link Aggregation IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3af Power over Ethernet IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 TELNET RFC 868 Time Protocol RFC 951 BOOTP RFC 1058 RIPv1 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1542 BOOTP Extensions RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2453 RIPv2 RFC 2548 (MS-RAS-Vendor only) RFC 3046 DHCP Relay Agent Information Option RFC 3576 Ext to RADIUS (CoA only) RFC 3768 VRRP RFC 4675 RADIUS VLAN & Priority UDLD (Uni-directional Link Detection) <p>IP multicast</p> <ul style="list-style-type: none"> RFC 3376 IGMPv3 (host joins only) 	<ul style="list-style-type: none"> RFC 3973 PIM Dense Mode RFC 4601 PIM Sparse Mode <p>IPv6</p> <ul style="list-style-type: none"> RFC 1981 IPv6 Path MTU Discovery RFC 2375 IPv6 Multicast Address Assignments RFC 2460 IPv6 Specification RFC 2464 Transmission of IPv6 over Ethernet Networks RFC 2710 Multicast Listener Discovery (MLD) for IPv6 RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only) RFC 3019 MLDv1 MIB RFC 3315 DHCPv6 (client and relay) RFC 3484 Default Address Selection for IPv6 RFC 3587 IPv6 Global Unicast Address Format RFC 3596 DNS Extension for IPv6 RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6 RFC 4022 MIB for TCP RFC 4087 IP Tunnel MIB RFC 4113 MIB for UDP RFC 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers RFC 4251 SSHv6 Architecture RFC 4252 SSHv6 Authentication RFC 4253 SSHv6 Transport Layer RFC 4254 SSHv6 Connection RFC 4291 IP Version 6 Addressing Architecture RFC 4293 MIB for IP RFC 4294 IPv6 Node Requirements RFC 4419 Key Exchange for SSH RFC 4443 ICMPv6 RFC 4541 IGMP & MLD Snooping Switch RFC 4861 IPv6 Neighbor Discovery RFC 4862 IPv6 Stateless Address Auto-configuration RFC 5095 Deprecation of Type 0 Routing Headers in IPv6 RFC 5340 OSPFv3 for IPv6 RFC 5453 Reserved IPv6 Interface Identifiers RFC 5519 Multicast Group Membership Discovery MIB (MLDv2 only) RFC 5722 Handling of Overlapping IPv6 Fragments <p>MIBs</p> <ul style="list-style-type: none"> IEEE 802.1ap (MSTP and STP MIB's only) RFC 1213 MIB II RFC 1493 Bridge MIB RFC 1724 RIPv2 MIB RFC 1850 OSPFv2 MIB RFC 2021 RMONv2 MIB RFC 2096 IP Forwarding Table MIB RFC 2613 SMON MIB RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2665 Ethernet-Like-MIB 	<ul style="list-style-type: none"> RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB RFC 2737 Entity MIB (Version 2) RFC 2787 VRRP MIB RFC 2863 The Interfaces Group MIB RFC 2925 Ping MIB RFC 2933 IGMP MIB <p>Network management</p> <ul style="list-style-type: none"> IEEE 802.1AB Link Layer Discovery Protocol (LLDP) RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) RFC 3176 sFlow ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) SNMPv1/v2c/v3 XRMON <p>OSPF</p> <ul style="list-style-type: none"> RFC 2328 OSPFv2 RFC 3101 OSPF NSSA RFC 3623 Graceful OSPF Restart (Unplanned Outages only) RFC 5340 OSPFv3 for IPv6 <p>QoS/CoS</p> <ul style="list-style-type: none"> RFC 2474 DiffServ Precedence, including 8 queues/port RFC 2597 DiffServ Assured Forwarding (AF) RFC 2598 DiffServ Expedited Forwarding (EF) <p>Security</p> <ul style="list-style-type: none"> IEEE 802.1X Port Based Network Access Control RFC 1492 TACACS+ RFC 2865 RADIUS (client only) RFC 2866 RADIUS Accounting RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP) Secure Sockets Layer (SSL) SSHv2 Secure Shell

HP 8200 zl Switch Series

Specifications (continued)



HP 8206-44G-PoE+-2XG v2 zl Switch with Premium Software (J9638A)



HP 8212-92G-PoE+-2XG v2 zl Switch with Premium Software (J9639A)

Included accessories	1 HP 8200 zl Management Module (J9092A) 2 HP 8200 zl Fabric Module (J9093A) 1 HP 8200 zl System Support Module (J9095A) 1 HP 1500W PoE+ zl Power Supply (J9306A) 1 HP 24-port Gig-T PoE+ v2 zl Module (J9534A) 1 HP 20-port Gig-T PoE+ / 2-port 10GbE SFP+ v2 zl Module (J9536A) 1 HP 8200 zl Switch Premium License (J9474A)	1 HP 8200 zl Management Module (J9092A) 2 HP 8200 zl Fabric Module (J9093A) 1 HP 8200 zl System Support Module (J9095A) 1 HP 8200 zl Switch Premium License (J9474A) 2 HP 1500W PoE+ zl Power Supply (J9306A) 3 HP 24-port Gig-T PoE+ v2 zl Module (J9534A) 1 HP 20-port Gig-T PoE+ / 2-port 10GbE SFP+ v2 zl Module (J9536A)
Ports	44 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 SFP+ 10-GbE ports; Duplex: full only 4 open module slots Supports a maximum of 144 autosensing 10/100/1000 ports or 48 10-GbE ports or 144 mini-GBICs, or a combination	92 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 SFP+ 10-GbE ports; Duplex: full only 8 open module slots Supports a maximum of 288 autosensing 10/100/1000 ports or 96 10-GbE ports or 288 mini-GBICs, or a combination
Power supplies	2 power supply slots 1 minimum power supply required includes: 1 x J9306A (HP 1500W PoE+ zl Power Supply)	4 power supply slots 2 minimum power supplies required includes: 2 x J9306A (HP 1500W PoE+ zl Power Supply)
Physical characteristics	17.42(w) x 17.49(d) x 10.35(h) in (44.25 x 44.42 x 26.29 cm) (6U height) Weight 61.49 lb (27.89 kg)	17.5(w) x 18.7(d) x 15.6(h) in (44.45 x 47.5 x 39.62 cm) (9U height) 102.76 lb (46.61 kg)
Memory and processor	Gigabit module ARM9 @ 200 MHz; packet buffer size: 144 Mb QDR SDRAM 10G module ARM9 @ 200 MHz; packet buffer size: 36 Mb QDR SDRAM Management module Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 128 MB compact flash, 256 MB DDR SDRAM	ARM9 @ 200 MHz; packet buffer size: 144 Mb QDR SDRAM ARM9 @ 200 MHz; packet buffer size: 36 Mb QDR SDRAM Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 128 MB compact flash, 256 MB DDR SDRAM
Mounting	Mounts in an EIA-standard 19 in telco rack/equipment cabinet (hardware included); horizontal surface mounting only. An optional 4-post cabinet rail is available (see ordering guide).	Mounts in an EIA-standard 19 in telco rack or equipment cabinet (hardware included); horizontal surface mounting only. An optional 4-post cabinet rail is available (see ordering guide).
Performance	1000 Mb Latency < 3.7 μs (FIFO 64-byte packets) 10 Gbps Latency < 2.1 μs (FIFO 64-byte packets) Throughput up to 369.6 million pps Routing/Switching capacity 496.8 Gbps Switch fabric speed 561.6 Gbps Routing table size 10000 entries MAC address table size 64000 entries	< 3.7 μs (FIFO 64-byte packets) < 2.1 μs (FIFO 64-byte packets) up to 739 million pps 993.6 Gbps 1.1 Tbps 10000 entries 64000 entries
Environment	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 15% to 95% @ 131°F (55°C), noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 15% to 95% @ 149°F (65°C), noncondensing Altitude up to 10,000 ft (3 km) Acoustic Power: 60.0 dB, Pressure: 41.3 dB; ISO 7779, ISO 9296	32°F to 113°F (0°C to 45°C) 15% to 95% @ 131°F (55°C), noncondensing -40°F to 158°F (-40°C to 70°C) 15% to 95% @ 149°F (65°C), noncondensing up to 10,000 ft (3 km) Power: 63.0 dB, Pressure: 47.8 dB; ISO 7779, ISO 9296
Electrical characteristics	Achieved Miercom Certified Green Award Description Chassis ships without power supplies. Two power supply slots are available; three different power supplies are available. See power supply products for additional specifications. Maximum heat dissipation 2450 BTU/hr (2584.75 kJ/hr), (max. non-PoE); 3700 BTU/hr (3903 kJ/hr) (max. PoE) Voltage 100-127/200-240 VAC Frequency 50/60 Hz Notes Power supplies must be ordered separately. A minimum of one J8712A, J8713A, or J9306A supply is required to power the system.	Achieved Miercom Certified Green Award Description Chassis ships without power supplies. Four power supply slots are available; three different power supplies are available. See power supply products for additional specifications. Maximum heat dissipation 4900 BTU/hr (5170 kJ/hr), (max. non-PoE); 7400 BTU/hr (7807 kJ/hr) (max. PoE) 100-127/200-240 VAC 50/60 Hz Power supplies must be ordered separately. A minimum of two J8712A, J8713A, or J9306A supplies are required to power the system.
Safety	CSA 22.2 No. 60950; UL 60950; IEC 60950; EN 60950; IEC 60825	CSA 22.2 No. 60950; UL 60950; IEC 60950; EN 60950; IEC 60825
Emissions	FCC Class A; FCC part 15 Class A; ICE-003, Canadian Radio Interface Regulation; VCCI Class A; EN 55022/CISPR 22 Class A	FCC Class A; FCC part 15 Class A; ICE-003, Canadian Radio Interface Regulation; VCCI Class A; EN 55022/CISPR 22 Class A

HP 8200 zl Switch Series

Specifications (continued)

	HP 8206-44G-PoE+-2XG v2 zl Switch with Premium Software (J9638A)	HP 8212-92G-PoE+-2XG v2 zl Switch with Premium Software (J9639A)
Immunity		
EN	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2; 4 kV CD, 8 kV AD	IEC 61000-4-2; 4 kV CD, 8 kV AD
Radiated	IEC 61000-4-3; 3 V/m	IEC 61000-4-3; 3 V/m
EFT/Burst	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)
Surge	IEC 61000-4-5; 1 kV/2 kV AC	IEC 61000-4-5; 1 kV/2 kV AC
Conducted	IEC 61000-4-6; 3 V	IEC 61000-4-6; 3 V
Power frequency magnetic field	IEC 61000-4-8; 1 A/m, 50 or 60 Hz	IEC 61000-4-8; 1 A/m, 50 or 60 Hz
Voltage dips and interruptions	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods
Harmonics	EN 61000-3-2, IEC 61000-3-2	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3	EN 61000-3-3, IEC 61000-3-3
Management	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)
Notes	Interface/Service modules, power supplies, and redundant management module must be ordered separately. RS-232C console port via an RJ-45 connector. Supported 1G SFP transceivers are revision "B" or later (product number ends with the letter "B" or later; for example, J9142B, J8177C).	Interface/Service modules, power supplies, and redundant management module must be ordered separately. RS-232C console port via an RJ-45 connector. Supported 1G SFP transceivers are revision "B" or later (product number ends with the letter "B" or later; for example, J9142B, J8177C).
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW442E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW443E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW444E)</p> <p>3-year, 24x7 SW phone support, software updates (UW445E)</p> <p>Installation with minimum configuration, system-based pricing (U4828E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4832E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW462E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW463E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW464E)</p> <p>4-year, 24x7 SW phone support, software updates (UW465E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UY921E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UY922E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY923E)</p> <p>5-year, 24x7 SW phone support, software updates (UY924E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW446E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW466E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UY925E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR609E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR610E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR613E)</p> <p>1-year, 24x7 software phone support, software updates (HR612E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR611E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS762E)</p> <p>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS763E)</p> <p>3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS764E)</p> <p>3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS765E)</p> <p>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS766E)</p> <p>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS767E)</p> <p>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS768E)</p> <p>5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS769E)</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW447E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW448E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW449E)</p> <p>3-year, 24x7 SW phone support, software updates (UW450E)</p> <p>Installation with minimum configuration, system-based pricing (U4828E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4832E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW467E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW468E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW469E)</p> <p>4-year, 24x7 SW phone support, software updates (UW471E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UY926E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UY927E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UY928E)</p> <p>5-year, 24x7 SW phone support, software updates (UY929E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UY937E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW472E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UY930E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR614E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR615E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR618E)</p> <p>1-year, 24x7 software phone support, software updates (HR617E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR616E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS754E)</p> <p>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS755E)</p> <p>3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS756E)</p> <p>3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS757E)</p> <p>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS758E)</p> <p>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS759E)</p> <p>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS760E)</p> <p>5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS761E)</p>

HP 8200 zl Switch Series

Specifications (continued)

	HP 8206-44G-PoE+-2XG v2 zl Switch with Premium Software (J9638A)	HP 8212-92G-PoE+-2XG v2 zl Switch with Premium Software (J9639A)
	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.
Standards and protocols (applies to all products in series)	<p>BGP</p> <p>RFC 1997 BGP Communities Attribute RFC 2918 Route Refresh Capability RFC 4271 A Border Gateway Protocol 4 (BGP-4) RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP) RFC 4724 Graceful Restart Mechanism for BGP RFC 5492 Capabilities Advertisement with BGP-4</p> <p>Denial of service protection</p> <p>CPU DoS Protection</p> <p>Device management</p> <p>RFC 1591 DNS (client) HTML and telnet management</p> <p>General protocols</p> <p>IEEE 802.1ad Q-in-Q IEEE 802.1AX-2008 Link Aggregation IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3af Power over Ethernet IEEE 802.3x Flow Control RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 TELNET RFC 868 Time Protocol RFC 951 BOOTP RFC 1058 RIPv1 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1542 BOOTP Extensions RFC 2030 Simple Network Time Protocol (SNTP) v4 RFC 2131 DHCP RFC 2453 RIPv2 RFC 2548 (MS-RAS-Vendor only) RFC 3046 DHCP Relay Agent Information Option RFC 3576 Ext to RADIUS (CoA only) RFC 3768 VRRP RFC 4675 RADIUS VLAN & Priority UDLD (Uni-directional Link Detection)</p> <p>IP multicast</p> <p>RFC 3376 IGMpv3 (host joins only)</p>	<p>RFC 3973 PIM Dense Mode RFC 4601 PIM Sparse Mode</p> <p>IPv6</p> <p>RFC 1981 IPv6 Path MTU Discovery RFC 2375 IPv6 Multicast Address Assignments RFC 2460 IPv6 Specification RFC 2464 Transmission of IPv6 over Ethernet Networks RFC 2710 Multicast Listener Discovery (MLD) for IPv6 RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only) RFC 3019 MLDv1 MIB RFC 3315 DHCPv6 (client and relay) RFC 3484 Default Address Selection for IPv6 RFC 3587 IPv6 Global Unicast Address Format RFC 3596 DNS Extension for IPv6 RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6 RFC 4022 MIB for TCP RFC 4087 IP Tunnel MIB RFC 4113 MIB for UDP RFC 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers RFC 4251 SSHv6 Architecture RFC 4252 SSHv6 Authentication RFC 4253 SSHv6 Transport Layer RFC 4254 SSHv6 Connection RFC 4291 IP Version 6 Addressing Architecture RFC 4293 MIB for IP RFC 4294 IPv6 Node Requirements RFC 4419 Key Exchange for SSH RFC 4443 ICMPv6 RFC 4541 IGMP & MLD Snooping Switch RFC 4861 IPv6 Neighbor Discovery RFC 4862 IPv6 Stateless Address Auto-configuration RFC 5095 Deprecation of Type 0 Routing Headers in IPv6 RFC 5340 OSPFv3 for IPv6 RFC 5453 Reserved IPv6 Interface Identifiers RFC 5519 Multicast Group Membership Discovery MIB (MLDv2 only) RFC 5722 Handling of Overlapping IPv6 Fragments</p> <p>MIBs</p> <p>IEEE 802.1ap (MSTP and STP MIB's only) RFC 1213 MIB II RFC 1493 Bridge MIB RFC 1724 RIPv2 MIB RFC 1850 OSPFv2 MIB RFC 2021 RMONv2 MIB RFC 2096 IP Forwarding Table MIB RFC 2613 SMON MIB RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2665 Ethernet-Like-MIB</p>
		<p>RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB RFC 2737 Entity MIB (Version 2) RFC 2787 VRRP MIB RFC 2863 The Interfaces Group MIB RFC 2925 Ping MIB RFC 2933 IGMP MIB</p> <p>Network management</p> <p>IEEE 802.1AB Link Layer Discovery Protocol (LLDP) RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events) RFC 3176 sFlow ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) SNMPv1/v2c/v3 XRMON</p> <p>OSPF</p> <p>RFC 2328 OSPFv2 RFC 3101 OSPF NSSA RFC 3623 Graceful OSPF Restart (Unplanned Outages only) RFC 5340 OSPFv3 for IPv6</p> <p>QoS/CoS</p> <p>RFC 2474 DiffServ Precedence, including 8 queues/port RFC 2597 DiffServ Assured Forwarding (AF) RFC 2598 DiffServ Expedited Forwarding (EF)</p> <p>Security</p> <p>IEEE 802.1X Port Based Network Access Control RFC 1492 TACACS+ RFC 2865 RADIUS (client only) RFC 2866 RADIUS Accounting RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP) Secure Sockets Layer (SSL) SSHv2 Secure Shell</p>

HP 8200 zl Switch Series accessories

Modules

HP 8-port 10GBASE-T v2 zl Module (J9546A)
HP 8-port 10GbE SFP+ v2 zl Module (J9538A)
HP 4-port 10GbE CX4 zl Module (J8708A)
HP 4-port 10GbE X2 zl Module (J8707A)
HP 4-port 10GbE SFP+ zl Module (J9309A)
HP 20-port Gig-T PoE+ / 2-port 10GbE SFP+ v2 zl Module (J9536A)
HP 20-port Gig-T / 2-port 10GbE SFP+ v2 zl Module (J9548A)
HP 20-port Gig-T PoE+ / 4-port SFP v2 zl Module (J9535A)
HP 20-port Gig-T / 4-port SFP v2 zl Module (J9549A)
HP 24-port SFP v2 zl Module (J9537A)
HP 12-port Gig-T PoE+ / 12-port SFP v2 zl Module (J9637A)
HP 24-port Gig-T PoE+ v2 zl Module (J9534A)
HP 24-port Gig-T v2 zl Module (J9550A)
HP 24-port 10/100/1000 PoE zl Module (J8702A)
HP 20-port Gig-T / 4-port Mini-GBIC zl Module (J8705A)
HP 24-port Mini-GBIC zl Module (J8706A)
HP 24-port 10/100 PoE+ v2 zl Module (J9547A)
HP 24-port 10/100 PoE+ zl Module (J9478A)
HP 24-port 10/100/1000 PoE+ zl Module (J9307A)
HP 20-port 10/100/1000 PoE+ / 4-port Mini-GBIC zl Module (J9308A)
HP 8200 zl System Support Module (J9095A)
HP 8200 zl Management Module (J9092A)
HP 8200 zl Fabric Module (J9093A)
HP Extended Services zl Module with Riverbed Steelhead RiOS™ Application (J9517A)
HP Survivable Branch Communication zl Module powered by Microsoft® Lync (J9485A)
HP Services zl Module for Avaya Aura Session Border Controller powered by Acme Packet (J9486A)
HP Threat Management Services zl Module with 1-year IPS Subscription Service (J9156A)
HP Threat Management Services zl Module (J9155A)
HP Services zl Module (J9289A)
HP Advanced Services zl Module (J9483A)
HP Advanced Services zl Module with Microsoft® Windows® Server 2008 R2 Standard (J9666A)
HP Advanced Services zl Module with Citrix XenServer platform (J9747A)
HP Advanced Services zl Module with VMware vSphere Platform (J9748A)

Transceivers

HP X131 10G X2 SC ER Transceiver (J8438A)
HP X131 10G X2 SC SR Transceiver (J8436A)
HP X131 10G X2 CX4 Transceiver (J8440C)
HP X111 100M SFP LC FX Transceiver (J9054C)
HP X131 10G X2 SC LR Transceiver (J8437A)
HP X131 10G X2 SC LRM Transceiver (J9144A)
HP X112 100M SFP LC BX-D Transceiver (J9099B)

HP X112 100M SFP LC BX-U Transceiver (J9100B)
HP X132 10G SFP+ LC SR Transceiver (J9150A)
HP X132 10G SFP+ LC LR Transceiver (J9151A)
HP X132 10G SFP+ LC LRM Transceiver (J9152A)
HP X121 1G SFP LC LH Transceiver (J4860C)
HP X121 1G SFP LC SX Transceiver (J4858C)
HP X121 1G SFP LC LX Transceiver (J4859C)
HP X121 1G SFP RJ45 T Transceiver (J8177C)
HP X122 1G SFP LC BX-D Transceiver (J9142B)
HP X122 1G SFP LC BX-U Transceiver (J9143B)
HP X132 10G SFP+ LC ER Transceiver (J9153A)

Cables

HP X242 10G SFP+ to SFP+ 1m Direct Attach Copper Cable (J9281B)
HP X242 10G SFP+ to SFP+ 3m Direct Attach Copper Cable (J9283B)
HP X242 10G SFP+ to SFP+ 7m Direct Attach Copper Cable (J9285B)
HP X244 10G XFP to SFP+ 1m Direct Attach Copper Cable (J9300A)
HP X244 10G XFP to SFP+ 3m Direct Attach Copper Cable (J9301A)
HP X244 10G XFP to SFP+ 5m Direct Attach Copper Cable (J9302A)
HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)
HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)
HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)
HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)
HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)
HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)
HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)
HP 0.5 m PremierFlex OM3+ LC/LC Optical Cable (BK837A)
HP 1 m PremierFlex OM3+ LC/LC Optical Cable (BK838A)
HP 2 m PremierFlex OM3+ LC/LC Optical Cable (BK839A)
HP 5 m PremierFlex OM3+ LC/LC Optical Cable (BK840A)
HP 15 m PremierFlex OM3+ LC/LC Optical Cable (BK841A)
HP 30 m PremierFlex OM3+ LC/LC Optical Cable (BK842A)
HP 50 m PremierFlex OM3+ LC/LC Optical Cable (BK843A)
HP X242 10G SFP+ to SFP+ 10m Direct Attach Copper Cable (J9286B)
HP X242 10G SFP+ to SFP+ 15m Direct Attach Copper Cable (J9287B)

Power Supply

HP 1500W PoE+ zl Power Supply (J9306A)
HP 1500W zl Power Supply (J8713A)
HP 875W zl Power Supply (J8712A)

License

HP 8200 zl Switch Premium License (J9474A)

Appliance

HP PCM+ Agent with ONE Services zl Module (J9496A)

HP 8206 zl Switch with Premium Software (J9640A)

HP 20-port Gig-T / 4-port SFP v2 zl Module (J9549A)
HP 8206 zl Switch Fan Tray (J9476A)

HP 8200 zl Switch Series accessories (continued)

HP 20-port Gig-T / 4-port SFP v2 zl Module (J9549A)
HP 20-port Gig-T / 4-port SFP v2 zl Module (J9549A)

HP 8212 zl Switch with Premium Software (J9641A)

HP 8212 zl Fan Tray (J9094A)
HP 20-port Gig-T / 4-port SFP v2 zl Module (J9549A)
HP 20-port Gig-T / 4-port SFP v2 zl Module (J9549A)

HP 8206-44G-PoE+-2XG v2 zl Switch with Premium Software (J9638A)

HP 20-port Gig-T / 4-port SFP v2 zl Module (J9549A)
HP 8206 zl Switch Fan Tray (J9476A)

HP 8212-92G-PoE+-2XG v2 zl Switch with Premium Software (J9639A)

HP 8212 zl Fan Tray (J9094A)



Products within this series have achieved sufficient scores in each of the rated criteria to achieve the Miercom Certified Green distinction Award. See the Specifications section of this series for more information.

To learn more, visit hp.com/networking

© Copyright 2009-2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation.

4AA2-7811ENW, Created July 2009; Updated September 2012, Rev. 9

