

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

2-Port Compact USB KVM Switch w/Audio and Cable

MODEL NUMBER: B004-VUA2-K-R







Description

The B004-VUA2-K-R is a 2-port Compact USB KVM Switch with optional audio and microphone switching function. It allows you to access, control, boot and reboot two USB-enabled computers from a single console (keyboard, monitor and mouse). The independent audio/mic switching function allows an uninterrupted audio experience - you can continue listening to audio even when you switch to the other computer.

It includes innovative, easy-to-use KVM Switcher Software for Windows and Macintosh platforms. A small client application facilitates your KVM switching operations such as computer selection, hot key sequence programming, auto-scanning, auto-scan delay time programming, independent or simultaneous audio/computer switching and more. Compatible with all major operating systems.

Features

- · Fast, easy switching via keyboard hot keys, push buttons or software
- Plug-and-play setup no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice]
- Compact design saves desk space
- Does not require an AC adapter
- Compatible with all major operating systems
- Includes two, 6ft Cable Kits

Highlights

- Fast, easy switching via keyboard hot keys, push buttons or software (not required)
- PC and Mac compatible
- Allows sharing of audio components between systems; listen to music from one computer while switching to the other computer
- Compact design saves desk
 space
- No AC adapter required
- (x2) 6ft USB KVM Cable kits and (x2) 6ft 3.5mm Audio Cable kits included
- Compatible with all major operating systems

Applications

 Use this KVM switch when accessing two USB-equipped computers with one monitor, keyboard and mouse.

System Requirements

- Console: VGA, SVGA or Multisync Monitor, USB Keyboard and USB Mouse
- Computers: VGA, SVGA or Multisync Monitor Port and USB Port
- Audio (Optional): Speakers with standard 3.5 mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

Package Includes

- Compact 2-port USB KVM Switch with Audio
- (2) 6ft USB KVM Cable Kits and
 (2) 6ft 3.5mm Audio Cable Kits
- CD-ROM with KVM Switcher Software



Specifications

RoHS	Y
OVERVIEW	
Users	1
Console	No
Port Control	Push Buttons, Hotkeys, Software
Max CPU	2
PC/Server Connections	PS/2
Cat5 KVM Switch	No
IP Remote Access	No
Style	Desktop
PHYSICAL	
Color	Black
LCD Monitor (in.)	Not Applicable
LCD Monitor (cm)	Not Applicable
ENVIRONMENTAL	
ENVIRONMENTAL	
Storage Temperature Range	-4° to 140° F (-20° to 40° C)
Storage Temperature	-4° to 140° F (-20° to 40° C) 32° to 104° F (0° to 40° C)
Storage Temperature Range	
Storage Temperature Range Operating Temperature	32° to 104° F (0° to 40° C)
Storage Temperature Range Operating Temperature BTUs	32° to 104° F (0° to 40° C)
Storage Temperature Range Operating Temperature BTUs CONNECTIONS	32° to 104° F (0° to 40° C) 17.065
Storage Temperature Range Operating Temperature BTUs CONNECTIONS Ports Included KVM Cable (Equipment Side) -	32° to 104° F (0° to 40° C) 17.065
Storage Temperature Range Operating Temperature BTUs CONNECTIONS Ports Included KVM Cable (Equipment Side) - Connector 1 Included KVM Cable (Equipment Side) -	32° to 104° F (0° to 40° C) 17.065 2 HD15 (Male)
Storage Temperature Range Operating Temperature BTUs CONNECTIONS Ports Included KVM Cable (Equipment Side) - Connector 1 Included KVM Cable (Equipment Side) - Connector 2 Included KVM Cable (Equipment Side) -	32° to 104° F (0° to 40° C) 17.065 2 HD15 (Male) USB A (Male)

Owner's Manual with Warranty
Information



Local Console Ports - Port 3	(x2) 3.5mm (Female)	
CERTIFICATIONS		
Certifications	FCC, CE, RoHS Compliant	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.