

2 Port SuperSpeed Mini PCI Express USB 3.0 Adapter Card w/ Bracket Kit and UASP Support StarTech ID: MPEXUSB3S22B

The MPEXUSB3S22B 2-Port Mini PCI Express USB 3.0 Card with Bracket Kit adds two external USB 3.0 ports to small form-fac/ 3.0 MÆC Â cc.B% M Fth) auscato .



At the same peak in testing, UASP also showed up to an 80% reduction in required processor resources.



Test results were obtained using an Intel® Ivy Bridge system, StarTech.com add-on USB 3.0 cards, a UASPenabled StarTech.com enclosure, and a SATA III solid state drive.

Applications

- System builders creating a small form factor HTPC with external USB 3.0 storage or other peripherals
- Add two USB 3.0 device connections to a mini-ITX or custom embedded system with no room for a standard PCI Express card
- Connecting external USB 3.0 storage devices for quick backup or archiving

www.startech.com
1 800 265 1844



Features

- Two external USB 3.0 type A ports
- UASP support for more efficient data transfer
- Provides up to 900mA of power per port
- Fully Compliant with USB 3.0 and Intel xHCI Specification
- Backward compatible with USB 2.0 and USB 1.0/1.1 devices
- PCI Express Base Specification 2.0 Compliant (backward compatible with 1.0a/1.1)
- Supports Control / Bulk / Interrupt / Isochronous USB Transfer Modes

www.startech.com
1 800 265 1844




Spec Sheet

Hard-to-find made easy*

Technical Specifications

Ports2InterfaceUSB 3.0Bus TypeMini PCI ExpressCard TypeEmbeddedIndustry StandardsIntel xHCI	
Bus TypeMini PCI ExpressCard TypeEmbedded	
Card Type Embedded	
Industry Standards Intel xHCI	
Industry Standards PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
Industry Standards USB 3.0	
Chipset ID Renesas - uPD720202	
Connector Type(s) 1 - Mini PCI Express x1 (52 pin) Male	
Internal Ports 1 - IDC (20 pin; USB 3.0; Motherboard Header) Male	
Internal Ports 1 - SP4 (4 pin; Small Drive Power) Male	
External Ports 2 - USB 3.0 A (9 pin; SuperSpeed) Female	
Maximum Data Transfer Rate 5 Gbps	
Type and Rate USB 3.0 - 5 Gbit/s	
UASP Support Yes	
OS Compatibility Windows® 8 / 8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64)	
Windows Server® 2012, 2008 R2, 2003	
System and Cable Requirements Available Mini PCI Express expansion slot (full length)	
System and Cable Requirements Case/Chassis with available Low or Full profile expansion card slot	
Cable Length 23.6 in [600 mm]	
Product Length 2 in [51 mm]	
Product Width 1.2 in [30 mm]	
Product Weight 2.2 oz [61 g]	
Operating Temperature 0°C to 55°C (32°F to 131°F)	
Storage Temperature -20°C to 85°C (-4°F to 185°F)	
Humidity 5~95% RH	
Shipping (Package) Weight 7.3 oz [207 g]	
Included in Package 1 - Mini PCIe USB 3.0 Card	
Included in Package 1 - USB Header to 2 Port Cable	
Included in Package 1 - Low Profile Bracket	
Included in Package 1 - Standard Profile Bracket	
Included in Package 1 - LP4 Power Cable	
Included in Package 1 - Screw Kit	





Included in Package Included in Package Spec Sheet

1 - Driver CD

1 - Instruction Manual

Certifications, Reports and Compatibility











www.startech.com 1 800 265 1844