DWC-2000 Unified Wireless Controller

Overview

The D-Link DWC-2000 Wireless Controller is a centralized Wireless LAN manager designed specifically for education, hospitality, and medium-to-large enterprises. Out of the box, it can manage up to 64 compatible D-Link Unified Wireless Access Points. With optional upgrade licenses, it can support up to 256 access points per controller, and up to 1,024 access points in a controller peer group, making it cost-effective mobility solution suitable for medium to large scale deployments. Features such as auto-managed AP discovery and single-point management allow users to achieve enterprise class networking without the burden of executing massive and complex configurations. The guest account generation function manages guest user bandwidth and accessibility to network resources. With a robust and comprehensive security detection system, the DWC-2000 manages associated APs by blocking potential attacks from unauthorized users and appliances, which is particularly crucial in wireless environments.

Simplified Deployment and Management

Using the Setup Wizard, the DWC-2000 can be configured for any network in minutes. Centralized management of remote access points via a simple interface provides the



DWC-2000 Unified Wireless Controller

Guest Control and Management

The DWC-2000 integrates guest management features that deliver a secure and easy solution for managing access to the Internet by temporary users in a private or public network. Each temporary account, or the issued ticket, is accompanied by time-limited or data-limited Internet access privileges. The Guest Management service allows batch generation of temporary accounts, and can also provide account details to the guest via printout. Furthermore, it can monitor or extend the usage on the specific account manually after account creation and activation. By connecting with payment gateways to authorized credit card or electronic payments, guests can easily purchase the service online.

Robust and Optimized Network

The DWC-2000 offers self-organizing, self-optimizing, and self-healing network capabilities to increase the stability of the entire wireless network. Maximum 4+4 wireless controller redundancy and AP provisioning automatically switches the AP management from the failed controller to the backup in emergency scenarios, giving your network the reliability it needs. Capable of regular radio scanning, the DWC-2000 can automatically tune radio channels and power from time to time to avoid interference and keep the wireless network optimized. To make up for a sudden RF signal vacuum created by a "dead" access point, the DWC-2000 increases the transmission output power of neighboring access points to expand RF coverage for a reliable, high performance network.

Comprehensive Security

The DWC-2000 provides a comprehensive wireless security solution for easy integration into any network. The Wireless Intrusion Detection System (WIDS) featured in the DWC-2000 detects rogue access points, rogue clients, and can anticipate wireless threats, to help prevent potential breaches and illegal access before any damage is done to the network. In addition to fundamental wireless security, the Captive Portal feature allows you to block clients from accessing the network until their identities are verified. The Captive Portal authentication servers cover local, RADIUS, LDAP, POP3 and Windows Active Directory. This double-layer authentication and authorization establish a robust security fence to avoid attacks from internal networks.

Technical Specifications

High Scalability, Availability, and Flexibility

To address today's fast-changing corporate structures, the DWC-2000 Wireless Controller offers flexible optional features: the administrator can purchase D-Link's Business Wireless Plus license packs to upgrade the DWC-2000's capabilities. D-Link offers a range of DWC-2000 managed AP license pack upgrades to increase the number of manageable access points, depending on need. By default, the DWC-2000 manages up to 64 access points, but this can be expanded to 256 access points per controller. With the DWC-2000, as business grows, so does its wireless network.

Limited Lifetime Warranty

D-Link offers a Limited Lifetime Warranty on the DWC-2000 Unified Wireless Controller to further its commitment to product quality and long-term customer confidence.

Network Implementation within L2/L3 Network in Medium to Large Environments.



Interface		
Ports	• 4 Gigabit RJ-45/SFP Combo Ports	
USB	• 2 USB 2.0 ports	
Console Port	• 1 RJ-45	
Expansion Slot	Reserved for future use	
Performance		
Maximum Access Points per Unit	• 64/256 ¹ (default/ upgrade)	



Maximum Access Points per peer group	• 256/ 1024 ¹ (default/ upgrade)	
Concurrent Captive Portal Authentication Users	• 3072	
Access Point Management		
Model of Managed APs	DWL-8610APDWL-8600APDWL-6600AP	DWL-3600APDWL-2600AP
AP Discovery & Control	Layer-2	Layer-3
AP Monitoring	Managed AP Rogue AP	Authentication Fail APStandalone AP
Client Monitoring	Authenticated Client Rogue Client	Authentication Fail ClientAd-hoc Client
Centralized RF/ Security Policy Management	Supported	
Roaming		
Fast Roaming	Supported	
Intra-controller/ Inter-controller Roaming	• Supported	
Intra-subnet/ Inter-subnet Roaming	Supported	
Security		
Wireless Security	WPA Personal/Enterprise	WPA2 Personal/Enterprise
Wireless Intrusion Detection & Prevention System (WIDS)	Rogue and Valid AP Classification	Rogue AP Mitigation
LAN Security	802.1x port-based access control and guest VLAN	
Authentication	Captive Portal	MAC Authentication
VLAN		
VLAN Group	• Up to 255 entries	
802.1q VLAN Tagging	• Supported	
Subnet-based VLAN	Supported	
Port-based VLAN	Supported	
User Account Management		
Permanent Account Authentication Method	 Local Database External RADIUS External LDAP 	 External POP3 External Windows Active Directory (wired only)
Temporary Account Authentication Method Local Database	Local Database	
Temporary Account Creation	Single or batch account generation by system with customized active or usage expired time	
Payment Gateway	Authorize.net Paypal	SecurePayWorld Pay

DWC-2000 Unified Wireless Controller

System Management		
Web-based User Interface	• HTTP	
Command Line	• Supported	
SNMP	• v1, v2c, v3	
Physical/Environmental		
Power Supply	• 100-240 V AC, 50-60 Hz Internal power supply	
Max. Power Consumption	• 26.95 W	
Dimensions	• 17.3 x 12.2 x 1.73 inches (440 x 310 x 44 mm)	
Operating Temperature	• 32 to 104 °F (0 to 40 °C)	
Storage Temperature	• -4 to 158 °F (-20 to 70 °C)	
Operating Humidity	• 5% to 95%, Non-condensing	
Emission (EMI)	FCC Class A, CE Class A, C-Tick, IC	
Safety	• cUL, LVD (EN60950-1)	
Warranty Information		
Warranty	Limited Lifetime ²	
Ordering Information		
Part Number	Description	
DWC-2000	Unified Wireless Controller	
Compatible D-Link Wireless Access Points		
DWL-8610AP	Unified Concurrent Dual-band Access Point 802.11a/b/g/n/ac	
DWL-8600AP	Unified Concurrent Dual-band Access Point 802.11a/b/g/n	
DWL-6600AP	Unified Concurrent Dual-band Access Point 802.11a/b/g/n	
DWL-3600AP	Unified Single-band Access Point 802.11b/g/n	
DWL-2600AP	Unified Single-band Access Point 802.11b/g/n	
AP License Upgrades		
DWC-2000-AP32-LIC	Enables management of 32 additional APs	
DWC-2000-AP64-LIC	Enables management of 64 additional APs	
DWC-2000-AP128-LIC	Enables management of 128 additional APs	

 $^{\rm l}$ The number of additional APs available for management depends on your license type. $^{\rm 2}$ Limited Lifetime Warranty available only in the USA.

Updated October 2014 v1

For more information

U.S.A. | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com

© 2014 D-Link. All Rights Reserved. D-Link and the D-Link logo are trademarks or registered trademarks of D-Link. Other trademarks or registered trademarks are the property of their respective owners.

Visit www.dlink.com for more details.

