



Features & Benefits

- High Density, single gang unit
- Available in a 2 or 4 port version
- Enhanced Category 5 performance
- No protruding leads
- Designed for direct wall mounting
- Custom logo service available

Specifications

| | |
|------------|--|
| Width | 87 mm |
| Depth | 27 mm |
| Height | 87 mm |
| Material | ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy |
| Finish | High gloss |
| IDC Colour | Code IDC colour code to T568B |
| IDC Blocks | Industry standard IDC blocks |
| PCB | 1.6 mm double sided PTH boards |
| Conforms | to ANSI/TIA-568-C Enhanced Category 5 Specification |

The Connectix 4000 Series offers Enhanced Category 5 performance in a High-Density package.

The Connectix 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires into a back box.

The 4000 Series Outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility. The position of the sockets on the Vertical Outlet allow for a compact installation without protruding leads.

Ordering Information

| Product Description | Part Number |
|---------------------------------------|----------------|
| CCS Cat 5e 4 Way Vertical Wall Outlet | 008-001-011-01 |
| CCS Cat 5e 2 Way Vertical Wall Outlet | 008-001-011-03 |

