

## 2 Port PCI Express SATA 6 Gbps eSATA Controller Card - Dual Port PCIe SATA III Card - 2 Int/2 Ext

StarTech ID: PEXESAT3221



The PEXESAT322I PCI Express SATA III Controller Card (6 Gbps) gives you the option to add 2 internal or external SATA ports to your computer, through a single PCI Express (x1) card slot. The card features on board jumper selection, which enables you to configure the card to provide 2 internal or external SATA III ports, or one of each, as needed.

The SATA III card features Port Multiplier (PM) support on each port, which allows multiple drives to be connected over a single cable when necessary to maximize the number of SATA device connections while reducing the amount of cabling required.

The card is fully compliant with the SATA revision 3.0 specification (up to 6Gbps of data bandwidth), enabling you to utilize the speeds of high performance hard drives and Solid State Drives (SSD), as well as SATA-based optical drives (CD-ROM, DVD-ROM, Blu-Ray).

The PEXESAT322I SATA III Controller card is backed by our 2-year manufacturer warranty and free lifetime technical support.

## **Applications**

- Upgrade an older PCIe-based system with SATA 6Gbps connectivity, to better utilize faster SATA drives
- Add more internal SATA ports to a computer system, for connecting additional storage drives and/or
  optical drives
- Add internal and/or external SATA III ports to a computer through a single PCI Express slot, with the
  option to change the available connections to external/internal, as needed based on updated system
  requirements or applications



## **Features**

- Two internal/external switchable SATA ports
- Compliant with SATA revision 3.0, which can support up to 6Gbps of bandwidth
- Support for SATA-based optical drives (CD/DVD/BD)
- Uses existing SATA I/II cabling
- Supports Native Command Queuing (NCQ) and ATA/ ATAPI commands
- Port Multiplier FIS-based and Command-based switching supported
- Compliant with PCI Express 2.0 standards
- Includes Low Profile/Half-Height installation bracket



## **Technical Specifications**

Warranty 2 Years

Ports 2

Interface eSATA & SATA
Bus Type PCI Express

Card Type Standard Profile (LP bracket incl.)

Port Style Integrated on Card
Chipset ID ASMEDIA ASM1061
Connector Type(s) 1 - PCI Express x1 Male
Internal Ports 2 - SATA (7 pin; Data) Plug
External Ports 2 - eSATA (7 pin; Data) Plug

Type and Rate SATA III (6 Gbps)

Port Multiplier Yes
LBA support 48-bit
RAID No

OS Compatibility Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista (32/64), XP (32/64)

Windows Server® 2012, 2008 R2, 2003

Product Length 4.8 in [121 mm]
Product Width 3.6 in [92 mm]
Product Height 0.8 in [20 mm]
Product Weight 1.6 oz [44 g]

Operating Temperature 0°C to 50°C (32°F to 122°F)
Storage Temperature -20°C to 60°C (-4°F to 140°F)

Humidity 5% ~ 85% RH Shipping (Package) Weight 5.3 oz [151 g]

Included in Package 1 - PCIe SATA Controller

Included in Package 1 - SATA Cable

Included in Package 1 - Low Profile Bracket

Included in Package 1 - Driver CD

Included in Package 1 - Instruction Manual





**Certifications, Reports and Compatibility** 











