

AXIS P33 Network Camera Series – Indoor models

Fixed domes for any environment with remote focus and zoom.



- > Exceptional image quality including 5MP and HDTV
- > WDR with dynamic capture
- > Lightfinder technology
- > Remote focus and zoom
- > P-Iris control
- > IK10 impact resistance

AXIS P33 Network Cameras constitute a series of indoor and outdoor-ready fixed domes. These cameras are ideal for unobtrusive video surveillance, day and night, in exposed areas such as airports, subways, retail stores, bank buildings, schools and university campuses. This document covers the indoor models of AXIS P33 Series.

AXIS P33 Series offers models with exceptional image quality from SVGA resolution up to 5 megapixel, including SMPTE standard compliant HDTV 720p and 1080p video. AXIS P33 Series provides multiple, individually configurable H.264 and Motion JPEG video streams.

The SVGA and HDTV 720p models support Axis' Lightfinder technology, which make these cameras extremely sensitive to low light. AXIS P3384-V that additionally supports wide dynamic range (WDR) with 'dynamic capture', provides outstanding video quality in the most demanding conditions with strong variations in light. The 5 megapixel model, AXIS P3367-V, can cover a large area with exceptional detail and light sensitivity. All AXIS P33 models support P-Iris control for optimal image clarity.

The remote focus capability allows for convenient

AXIS P33 Series has low, environmental-friendly power consumption, supplied by standard Power over Ethernet (IEEE 802.3af).



Fixed domes designed for efficient installation

Indoor models of AXIS P33 Series are the perfect choice for a wide range of demanding video applications. AXIS P33 Network Cameras are designed for professional video surveillance with easy and reliable installation in focus.

Lightfinder technology

The SVGA and HDTV 720p models of AXIS P33 Series incorporate Axis' unique Lightfinder technology. The outstanding light sensitivity, with maintained colors even in very poor lighting conditions, is obtained by a combination of Axis' expertise in image processing, system-on-chip development and selection of the best optical components.

For more on Lightfinder technology, go to:

www.axis.com/corporate/corp/tech_papers.htm

Wide dynamic range – dynamic capture

AXIS P3384-V that supports WDR with 'dynamic capture' is ideal for surveillance in areas with strong variations in light, for instance close to large windows and entrances, where the sunlight creates both very bright zones and dark shadows. AXIS P3384-V enables easy and clear identification of people and objects both in bright and dark areas.

P-Iris control

AXIS P33 Series features the advanced precise iris control that comprises a special P-Iris lens, together with dedicated software in the camera, to set the best iris position for optimal depth of field, resolution, image contrast and clarity. Good depth of field implies that objects at different distances from the camera are in focus simultaneously.

For more on P-Iris and iris control, go to:

www.axis.com/corporate/corp/tech_papers.htm

Easy installation with remote focus and zoom

AXIS P33 Network Cameras offer unique installation capabilities including remote focus and zoom. The remote focus feature enables convenient focusing over the network, eliminating the need for hands-on fine-tuning at the camera. The remote zoom functionality ensures that the camera's angle of view is optimized for the area to be monitored.

Unique pixel counter feature

The unique pixel counter offered in Axis cameras allows the installer to easily verify that the camera installation fulfills any regulatory or specific customer requirements on pixel resolution, ensuring, for instance, that there are enough pixels in the human face for facial identification.



Mounting options

AXIS P33 Series offers a wide range of optional kits for indoor installations, for example, for mounting on a wall, pole or corner. The IP51-rated drop ceiling mount kit protects the camera from condensation and dust that may exist in the plenum space above the drop ceiling. They include a smoked transparent cover as an alternative to the clear cover, for additional flexibility.



Technical specifications – AXIS P33 Network Camera Series, indoor models

Camera		Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264
Indoor models	AXIS P3353: SVGA, Lightfinder, tamper resistance AXIS P3354: 1 MP, Lightfinder, tamper resistance AXIS P3363-V: SVGA, Lightfinder, vandal resistance, audio, I/O ports AXIS P3364-V: 1 MP, Lightfinder, vandal resistance, audio, I/O ports 6 mm and 12 mm as suffix refers to lens model AXIS P3384-V: 1 MP, WDR – dynamic capture, Lightfinder, vandal resistance, audio, I/O ports AXIS P3346: 3 MP, multi-view, audio, I/O ports AXIS P3346-V: 3 MP, multi-view, vandal resistance, audio, I/O ports AXIS P3367-V: 5 MP, multi-view, vandal resistance, audio, I/O ports <i>Note: AXIS P3301-V and AXIS P3304-V are not part of AXIS P33 Series</i>	Multi-view streaming	AXIS P3346/P3346-V/P3367-V: Up to 8 individually cropped out view areas AXIS P3346/-V: When streaming 4 view areas and 1 overview in VGA resolution, the frame rate is 20 fps per stream (3 MP capture mode) AXIS P3367-V: When streaming 4 view areas and 1 overview in VGA resolution, the frame rate is 12 fps per stream (5 MP capture mode) or 20 fps per stream (3 MP capture mode)
Image sensor	AXIS P3353/P3363-V: Progressive scan RGB CMOS 1/3" AXIS P3354/P3364-V: Progressive scan RGB CMOS 1/3" AXIS P3384-V: Progressive scan RGB CMOS 1/3" AXIS P3346/-V: Progressive scan RGB CMOS 1/3" (effective) AXIS P3367-V: Progressive scan RGB CMOS 1/3.2"	Pan/Tilt/Zoom	Digital PTZ, preset positions, guard tour
Lens	Varifocal, remote focus and zoom, IR corrected, P-Iris control, megapixel resolution AXIS P3353/P3354/P3363-V/P3364-V 6 mm: 2.5-6 mm, 105° – 49° view*, F1.2 AXIS P3353/P3354/P3363-V/P3364-V 12 mm: 3.3-12 mm, 82° – 24° view*, F1.4 AXIS P3384-V: 3-9 mm, 84° – 30° view*, F1.2 AXIS P3346/-V: 3-9 mm, 84° – 30° view*, F1.2 AXIS P3367-V: 3-9 mm, 84° – 30° view*, F1.2 *horizontal angle of view	Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, exposure zones, backlight compensation, WDR – dynamic contrast, fine tuning of low light behavior Rotation: 0°, 90°, 180°, 270°, including Corridor Format AXIS P3384-V: WDR – dynamic capture: Up to 120 dB (0.5 – 500,000 lux) depending on scene
Day and night	Automatically removable infrared-cut filter	Audio (AXIS P3363-V/P3364-V/P3384-V/P3346/-V/P3367-V)	
Minimum illumination	AXIS P3353/P3354/P3363-V/P3364-V 6 mm: Color: 0.1 lux, F1.2, B/W: 0.02 lux, F1.2 AXIS P3353/P3354/P3363-V/P3364-V 12 mm: Color: 0.15 lux, F1.4, B/W: 0.03 lux, F1.4 AXIS P3384-V: Color: 0.5 lux, F1.2, B/W: 0.08 lux, F1.2 with dynamic capture Color: 0.15 lux, F1.2, B/W: 0.03 lux, F1.2 with Lightfinder AXIS P3346/-V: Color: 0.5 lux, F1.2, B/W: 0.08 lux, F1.2 AXIS P3367-V: Color: 0.2 lux, B/W: 0.04 lux, F1.2	Audio streaming	Two-way
Shutter time	AXIS P3353/P3354/P3363-V/P3364-V: 1/24500 s to 2 s with power line frequency 50 Hz, 1/29500 s to 2 s with power line frequency 60 Hz AXIS P3384-V: Dynamic capture: 1/192 s to 1/37 s with power line frequency 50 Hz, 1/231 s to 1/44 s with power line frequency 60 Hz; Lightfinder: 1/24500 s to 2 s with power line frequency 50 Hz, 1/29500 s to 2 s with power line frequency 60 Hz AXIS P3346/-V: 1/35500 s to 1/6 s AXIS P3367-V: 1/28000 s to 2 s	Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate
Camera angle adjustment	AXIS P3353/P3354/P3363-V/P3364-V: Pan 360°, tilt 170°, rotation 340° AXIS P3346/P3384-V/P3346-V/P3367-V: Pan 360°, tilt 160°, rotation 340°	Audio input/output	External microphone input or line input, line output Built-in microphone (can be disabled)
Video		Network	
Video compression	H.264 Baseline and Main Profile (MPEG-4 Part 10/AVC) Motion JPEG	Security	Password protection, IP address filtering, digest authentication, user access log, IEEE 802.1X** network access control, HTTPS** encryption
Resolutions	AXIS P3353/P3363-V: 800x600 (SVGA) to 160x90 AXIS P3354/P3364-V: 1280x960* (approx. 1.3 MP) to 160x120 AXIS P3384-V: 1280x960* (approx. 1.3 MP) to 160x120 AXIS P3346/-V: 2048x1536 (3 MP) to 160x90 AXIS P3367-V: 2592x1944 (5 MP) to 160x90 *1400x1050 (1.4 MP) scaled resolution available via VAPIX®	Supported protocols	IPv4/v6, HTTP, HTTPS**, SSL/TLS**, QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS
Frame rate H.264/ Motion JPEG	AXIS P3353/P3354/P3363-V/P3364-V/P3384-V: 25 fps with power line frequency 50 Hz, 30 fps with power line frequency 60 Hz AXIS P3346/-V: 3 MP capture mode: 20 fps in all resolutions, HDTV 1080p (1920x1080) and 2 MP 4:3 (1600x1200) capture modes: 30 fps in all resolutions AXIS P3367-V: 5 MP capture mode: 12 fps in all resolutions; and capable of all AXIS P3346/-V capture modes	System integration	
		Application Programming Interface	Open API for software integration, including the ONVIF specification available at www.onvif.org , as well as VAPIX® and AXIS Camera Application Platform from Axis Communications, specifications available at www.axis.com Support for AXIS Video Hosting System (AVHS) with One-Click Camera connection
		Intelligent video	Video motion detection, active tampering alarm Support for AXIS Camera Application Platform enabling installation of additional applications AXIS P3363-V/P3364-V/P3384-V/P3346/-V/P3367-V: Audio detection
		Event triggers	Intelligent video, edge storage events AXIS P3363-V/P3364-V/P3384-V/P3346/-V/P3367-V: External input
		Event actions	File upload: FTP, HTTP, network share and email Notification: email, HTTP and TCP Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, guard tour AXIS P3363-V/P3364-V/P3384-V/P3346/-V/P3367-V: External output activation, audio recording to edge storage, play audio clip
		Data streaming	Event data
		Built-in installation aids	Remote zoom, remote focus, pixel counter

** This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org)

Dimensions and weight – AXIS P33 Network Camera Series, indoor models

	<p>AXIS P3353 and AXIS P3354 Weight: 430 g (0.9 lb.) AXIS P3363-V/P3364-V Weight: 650 g (1.4 lb.)</p> 		<p>AXIS P3346 Weight: 490 g (1.1 lb.) AXIS P3384-V/P3346-V/P3367-V Weight: 700 g (1.6 lb.)</p>  <p>AXIS P3346: 101 mm (4.0") Vandal-resistant models: 104 mm (4.1")</p>
--	--	---	--

Accessories – AXIS P33 Network Camera Series, indoor models

Optional accessories for indoor models

IP51-rated drop-ceiling mount kit with transparent or smoked cover



Mounting bracket



Pendant adapter kit



AXIS T91A Brackets



AXIS Camera Companion (included),
 AXIS Camera Station and video
 management software from Axis'
 Application Development Partners (not
 included). For more information, see
www.axis.com/products/video/software